

DIMPLED SHEET DELTA®-NB

With its excellent performance record, this dimpled sheet offers outstanding safety in building construction and civil engineering. It is equally suitable for use as a sub-base course, a foundation liner, a seepage layer in double-wall structures, and below screed, where DELTA®-NB offers protection from rising damp.

Product Properties

Material	Special high-density PE, plasticizer-free, fully recyclable.
Colour	Black
Flat edge	Yes
Dimple height	approx. 8 mm
Dimple count	> 1,800
Diagonal dimple structure	For straight-line creasing and precise corner formation.
Air gap between dimples	approx. 5.3 l/m ²
Contact area dimples/substrate	approx. 1,450 cm ² /m ²
Compressive strength	approx. 200 kN/m ² ~ approx. 20 t/m ²
Operating temperature range	- 30 °C to + 80 °C
Chemical properties	Resistant to chemicals and root penetration, rot-proof, non-polluting for drinking water.
Roll size	20 m x 1.0 m, 20 m x 1.5 m, 20 m x 2.0 m, 20 m x 2.4 m, 20 m x 3.0 m
Packing units	15 rolls per pallet for sheets 1.0 m, 1.5 m or 2.0 m wide. 35 rolls per pallet for sheets 2.4 m or 3.0 m wide.
Handy accessories	DELTA®-NOPPENBAHNEN-PROFIL DELTA®-HAFTNAGEL DELTA®-MS DÜBEL DELTA®-MS KNOPF DELTA®-MULTIFIXX