

DELTA® protects property

DELTA®

DELTA®-MAXX

The flame-resistant membrane for pitched roofs




European fire class

B

flame-resistant
to EN 13501-1

DELTA®-MAXX

The flame-resistant membrane for pitched roofs



DELTA®-MAXX – the essentials in brief

Material	Moisture-storing polyester fabric with watertight vapour-permeable PU coating
Suitability	For fully insulated pitched roofs. With moisture retaining surface.
Flammability	European fire class B-s1,d2, EN 13501-1 (depending on the substrate)
Tear strength	approx. 450/300 N/5 cm, EN 12311-1+2
Watertightness	Class W1, EN 13859-1+2
S_d-value	approx. 0.15 m, EN ISO 12572
Thermal stability	-40 °C to +80 °C
Short-term maximum thermal load	+120 °C
Resistance to driving rain	Passed: driving rain test, sarking membranes and underlay sheets – Technical University of Berlin
Weight	approx. 190 g/m ²
Roll weight	approx. 14 kg
Roll dimensions	50 m × 1.50 m

Accessories



DELTA®-MULTI-BAND



DELTA®-THAN



DELTA®-FLEXX-BAND



DELTA®-SCHAUM-BAND SB 60

M
by Dörken GmbH & Co. KG, D-58311 Herdecke

Advantages at a glance

- ▶ DELTA®-MAXX fulfils the requirements of European fire class B.
- ▶ Extremely puncture proof, fulfils Employer's Liability Insurance Association criteria for fall-through safety.
- ▶ Highly elastic and stretchable for the best-possible installation quality.
- ▶ Vapour-permeable and water-repellent polyurethane coating as well as moisture-storing backing fabric for the best-possible protection against moisture.
- ▶ 30 years of experience with superior product and material quality flowed into the development of DELTA®-MAXX.
- ▶ Fitted out with DELTA®-AMS and DELTA®-BiCo.

DELTA®-MAXX – permanently reliable safety:



Long-term protection against ageing



Breathable – releases moisture



Resistant to driving rain



Facilitates windtight constructions



Thermally stable up to 120°C



Fall-through proof when laying



Very high UV protection

**flame-
resistant
membrane**



Dörken GmbH & Co. KG
Wetterstraße 58
58313 Herdecke

- +49 23 30/63-636
- +49 23 30/63-357
- bvf@doerken.de
- www.doerken.com/int
-  

A member of **DÖRKEN**GROUP



For further information material
visit our website and select Downloads



To find the right contact
partners for sales and technology
visit our website and select Contact



PEFC™ PEFC certified
This paper comes from sustainably managed forests and controlled sources