



555 VarioGel

The solution for exterior surfaces -
highly thixotropic transparent
medium-layer varnish



Ideal for dimensionally stable and limited dimensionally stable wooden construction elements

Gel-like, allows non-dripping smooth applications and maintains the original structure of the surface

Triple weather protection: protection against UV and humidity, film protection against algae and fungi

Fast drying

YOU SIMPLY DESERVE IT.

LUCITE® 555 VarioGel

Usable anywhere and
anytime of the year!

GEL-LIKE AND VERY EASY TO APPLY

The long pot-life allows applications without lap-marks even on large exterior surfaces.

The thixotropic one-pot system can easily be applied on surfaces overhead thanks to its non-dripping texture.



» FIRST-CLASS QUALITY

The high-quality long-oil alkyd resin protects exterior wooden surfaces for a long time. The satin finish not only embellishes but also increases the resistance of dimensionally stable and limited dimensionally stable wooden construction elements such as facades, roof eaves, carports, balconies, pergola etc. as well as windows and doors.



HIGHEST EFFICIENCY EVEN VERY EARLY IN THE YEAR.

- » The fast drying allows the application of two coats a day.
- » The second coat can be applied after 6 hours.
- » High covering power up to 8-10 m²/l.
- » Safe application even with low temperatures in spring or autumn.

TRIPLE PROTECTION AGAINST THE IMPACT OF WIND AND WEATHER:

- » Pigments protecting against UV and UV inhibitors offer higher protection against UV radiation and at the same time prevent an early greying of wooden surfaces.
- » The humidity regulating weather resistant membrane makes the surface water-repellent and thereby prevents infestation by vegetation.
- » The integrated film protection against algae and fungi increases the durability of the varnished wood.



The transparent varnish maintains the natural beauty of the wood.

SPECIAL SEMI-COVERING WHITE

- » The bright white colour (1111 pure white) increases the resistance of the wood thanks to its high content of white pigments.
- » UV inhibitors reduce the yellowing of wooden construction elements in shaded areas.
- » The transparent varnish restores old and weathered surfaces.

☒ DECORATIVE WOOD PROTECTION

- » 17 colours: from transparent colours type „real wood“ to the colours used by modern architecture.
- » The natural structure of the wood remains visible even after the application of the varnish

Classical „real wood“ colours



1111 pure white



8270 nut



2335 pinewood



8320 teak



6570 light oak



8450 palisander



8170 walnut



9995 ebony

Architectural colours



5449 powder blue



6486 fir green



3180 falun red

GREYWOOD colours



7360 alpine grey



7365 volcano grey



7380 quarz grey

Natural colours



9101 steppe



9102 olive



9103 sandalwood

Due to printing technique reasons the colours here reproduced may slightly deviate from the original colours. For your colour selection please refer to the LUCITE® Colour Fan which shows the original colours. Depending on the type of wood and application method colours may deviate in intensity therefore we recommend to test the product on a sample area before starting the application cycle.



Product Information LUCITE® 555 VarioGel

| | |
|--|--|
| Type of Product | Solvent containing thixotropic transparent medium-layer varnish with film protection, based on alkyd resin |
| Intended Use | For a wide range of applications on exterior surfaces (for example on facades, roof eaves, carports, balconies, pergola etc., windows and doors). The satin one-pot system increases the resistance of surfaces conferring a highly transparent finish which perfectly maintains the structure of the original surface. |
| Product Properties | <ul style="list-style-type: none">» highly thixotropic viscosity» especially long pot-life» the fast drying allows the application of two coats a day» film protection against algae and fungi» UV inhibitors ensure a long-lasting protection» the semi-covering colour white reliably isolates brown colouring substances contained in the wood thereby preventing surface discoloration» maintains the structure of the surface perfectly |
| Spreading Rate | approx. 8–10 m ² /l |
| Gloss angle 60° | satin gloss |
| Drying time with 20°C and 60% of relative humidity | dust dry after 2 hours / can be painted over after 6 hours |
| Containers | 1l / 2.5l |
| Colours | 17 colours according to the LUCITE® Colour Fan |
| Mix Colour Collections | RAL / NCS |
| Recommended Tools and Equipment | High-quality brushes for the application of transparent varnishes |

