Page 1/13

*

Safety Data Sheet

acc. to OSHA HCS

Printing date Jan 25, 2023

Reviewed on Jan 25, 2023

DÖRKEN

1 Identification	
Product identifier	
Trade name: CWS WERTLACK® Cowirant Brilliant	
Application of the substance / the mixture Coating agent Uses advised against This product is not suitable for uses other than those specified in the "Use of the substance/n particular manner of use is not listed, please contact the creator of this safety data sheet.	nixture". If your
Details of the supplier of the safety data sheet Manufacturer/Supplier: Dörken Coatings GmbH & Co. KG Wetterstr. 58 58313 Herdecke Germany www.doerkencoatings.de	
Phone: +49 2330 63 243 Fax: +49 2330 63 100 243	
Information department: msds.coatings@doerken.de	
Emergency telephone number: GBK/Infotrac ID 114993: (USA domestic) 1 800 535 5053	
Ollererd(a) identification	
2 Hazard(s) identification	
Classification of the substance or mixture GHS02 Flame Flammable Liquids 3 H226 Flammable liquid and vapor.	
Label elements GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms	
GHS02	
Signal word Warning Hazard statements Flammable liquid and vapor. Precautionary statements Keep away from heat/sparks/open flames/hot surfaces No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	(Contd. on page 2)

acc. to OSHA HCS

DÖRKEN

Printing date Jan 25, 2023

Reviewed on Jan 25, 2023

Trade name: CWS WERTLACK® Cowirant Brilliant

	(Contd. of pag
	autionary measures against static discharge.
	ective gloves/protective clothing/eye protection/face protection.
•	or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
	fire: Use CO2, powder or water spray to extinguish.
	well-ventilated place. Keep cool.
•	contents/container in accordance with local/regional/national/international regulations.
	tion system:
NFPA ratii	ngs (scale 0 - 4)
	Health = 0
2	Fire = 2
	Reactivity = 0
HIMIS-ratir	ngs (scale 0 - 4)
HEALTH	❶ Health = 0
FIRE	2 Fire = 2
REACTIVITY	0 Reactivity = 0
	—
Other haza	
•	f the product are heavier than air and may accumulate below ground level, in pits, channels and
	s in higher concentration.
•	an form explosive mixtures with air.
Results of	FPBT and vPvB assessment
PBT: Not a	
vPvB: Not	applicable.

*

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

0	•	
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	≥25-≤50%
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	10-25%
34590-94-8	Dipropylene glycol monomethyl ether	<5%

Additional information:

All hydrocarbons used comply with note P (less than 0.1% benzene) of the CLP regulation. For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

Description of first aid measures

General information:

In all cases of doubt, or when symptoms persist, seek medical advice.

Soiled, soaked clothes immediately take off.

Never give anything by mouth to an unconscious person.

(Contd. on page 3)

US

acc. to OSHA HCS

Printing date Jan 25, 2023

Trade name: CWS WERTLACK® Cowirant Brilliant

After inhalation: Supply fresh air; consult doctor in case of complaints. After skin contact: Wash with plenty of soap and water. After eye contact: Remove contact lenses. Keep eye lids open and rinse plentifully for at least 10 minutes with clean running water. Subsequently consult an ophthalmologist.

In case of troubles or persistent symptoms, consult an opthalmologist.

After swallowing:

Rinse out mouth and then drink plenty of water.

Seek immediate medical advice.

Information for doctor:

Most important symptoms and effects, both acute and delayed

Prolonged/repetitive skin contact may cause skin defattening or dermatitis. Headache, dizziness, numbness, sickness/nausea, tiredness, stunning effect, dry skin, allergic reactions.

Indication of any immediate medical attention and special treatment needed Symptomatic treatment.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents:

Extinguishing powder, foam, carbon dioxide. Use fire fighting measures that suit the environment. **For safety reasons unsuitable extinguishing agents:** Water with full jet

Special hazards arising from the substance or mixture

Flammable liquid and vapor.

Can form explosive gas-air mixtures.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Fire will produce dangerous decomposition products like dense, black smoke, carbon dioxide (CO₂), carbon monoxide (CO) and nitrogen oxides (NOx). Inhalation may cause serious health damage. Under certain fire conditions, traces of other toxic gases cannot be excluded.

Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device. Wear fully protective suit.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources and ensure a well-ventilated room. Do not inhale fumes. Avoid contact with skin and eyes.

(Contd. on page 4)

us -



(Contd. of page 2)

Reviewed on Jan 25, 2023

acc. to OSHA HCS

Printing date Jan 25, 2023

Reviewed on Jan 25, 2023

Trade name: CWS WERTLACK® Cowirant Brilliant (Contd. of page 3) **Environmental precautions:** Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of the collected material according to regulations. **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. **Protective Action Criteria for Chemicals** PAC-1: 34590-94-8 Dipropylene glycol monomethyl ether 150 ppm 1330-20-7 xylene (mix) 130 ppm 111-90-0 2-(2-ethoxyethoxy)ethanol 75 ppm 26896-20-8 2-ethyl-2,5-dimethylhexanoic acid 6 mg/m³ 85-44-9 phthalic anhydride 18 mg/m³ 108-65-6 2-Methoxy-1-methylethyl acetate 50 ppm 112-34-5 2-(2-Butoxyethoxy)ethanol 30 ppm 98-83-9 2-phenylpropene 100 ppm PAC-2: 34590-94-8 Dipropylene glycol monomethyl ether 1700* ppm 1330-20-7 xylene (mix) 920* ppm 111-90-0 2-(2-ethoxyethoxy)ethanol 100 ppm 26896-20-8 2-ethyl-2,5-dimethylhexanoic acid 66 mg/m³ 85-44-9 phthalic anhydride 56 mg/m³ 108-65-6 2-Methoxy-1-methylethyl acetate 1,000 ppm 112-34-5 2-(2-Butoxyethoxy)ethanol 33 ppm 98-83-9 2-phenylpropene 830 ppm PAC-3: 34590-94-8 Dipropylene glycol monomethyl ether 9900** ppm 1330-20-7 xylene (mix) 2500* ppm 111-90-0 2-(2-ethoxyethoxy)ethanol 450 ppm 26896-20-8 2-ethyl-2,5-dimethylhexanoic acid 400 mg/m³ 85-44-9 phthalic anhydride 10,000 mg/m³ 108-65-6 2-Methoxy-1-methylethyl acetate 5000* ppm 112-34-5 2-(2-Butoxyethoxy)ethanol 200 ppm (Contd. on page 5)

DÖRKEN

acc. to OSHA HCS

Printing date Jan 25, 2023

Trade name: CWS WERTLACK® Cowirant Brilliant

98-83-9 2-phenylpropene

7 Handling and storage

Handling:

Precautions for safe handling

Avoid the formation of ignitible and explosion- hazardous solution vapours.

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Material can become charged elektrostatically. Anti-static clothing including shoes are recommended.

Avoid contact with skin and eyes as well as inhalation of vapours.

Avoid the handling of incompatible substances and mixtures. Incompatible substances: see section 10.5

Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Make sure spills can be contained, e.g. in sump pallets.

Protect from frost, heat and direct sunlight. Keep tightly closed, cool and dry.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions: None.

Storage class: 3

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems:

Ensure a good ventilation. This can be achieved by local exhaustion or general exhaust air.

Control parameters

Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

3459	0-94-8 Dipropylene glycol monomethyl ether
PEL	Long-term value: 600 mg/m³, 100 ppm
	Chin

- REL Short-term value: 900 mg/m³, 150 ppm Long-term value: 600 mg/m³, 100 ppm Skin
- TLV Long-term value: 50 ppm

Regulatory information

PEL: Guide to Occupational Exposure Values (OSHA PELs) REL: Guide to Occupational Exposure Values (NIOSH RELs)

TLV: Guide to Occupational Exposure Values (TLV)

(Contd. on page 6)

US





(Contd. of page 4)

5000* ppm

acc. to OSHA HCS

Printing date Jan 25, 2023

Reviewed on Jan 25, 2023

DÖRKEN

(Contd. of page 5)

Trade name: CWS WERTLACK® Cowirant Brilliant

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls Provide good ventilation and/or an exhaust system in the work area.

Personal protective equipment: General protective and hygienic measures: Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Immediately remove all soiled and contaminated clothing. Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection.

Breathing equipment:

Use always breathing protection with splashing medium. Use combination filter type A(-P2) according to EN 141.

Protection of hands:

Work with gloves. Gloves must be inspected for damage before use. Defective or damaged gloves must not be used. Gloves must satisfy the specifications of EC directive 89/686/EWG and standard EN 374.

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Tightly sealed goggles Have eye wash bottle or eye rinse ready at work place.

Body protection: Solvent resistant protective clothing

Information on basic phys	ical and chemical properties	
General Information		
Appearance:		
Form:	Fluid	
Color:	Colorless	
Odor:	Weak after aliphatic hydrocarbons	
Odor threshold:	For mixtures not applicable.	
pH-value:	Mixture is non-soluble (in water).	

acc. to OSHA HCS

Printing date Jan 25, 2023

Reviewed on Jan 25, 2023

DÖRKEN

Trade name: CWS WERTLACK® Cowirant Brilliant

	(Contd. of page
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Not security-related. 145-205 °C (293-401 °F)
Flash point:	54 °C (129.2 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	>200 °C (>392 °F)
Decomposition temperature:	For mixtures not applicable.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vap mixtures are possible.
Explosion limits: Lower: Upper:	0.6 Vol % 7 Vol %
Oxidizing properties	The product is flammable, although not oxidising.
Vapor pressure at 20 °C (68 °F): Density at 20 °C (68 °F):	3 hPa (2.3 mm Hg) 0.87-0.93 g/cm³ (7.26-7.761 lbs/gal)
Vapor density	Not applicable.
Evaporation rate	For mixtures not applicable.
Solubility in / Miscibility with Water: polar solvents: non-polar solvents:	Not miscible or difficult to mix. Not miscible or difficult to mix. Fully miscible.
Partition coefficient (n-octanol/wat	er): For mixtures not applicable.
Viscosity:	> 90 s (20°C / DIN 53211 / 4 mm) > 60 s (20°C / ISO 2431 / 6 mm) > 20,5 mm²/s (40°C)
Solvent content: VOC content:	53.5-<53.84 %
Other information	No further relevant information available.

10 Stability and reactivity

Reactivity Vapours can form explosive mixtures with air.
Chemical stability Product is stable under normal storage conditions.
Possibility of hazardous reactions
No dangerous reactions known.
No dangerous reactions are known.

(Contd. on page 8)

US

acc. to OSHA HCS

Printing date Jan 25, 2023

Reviewed on Jan 25, 2023

DÖRKEN

(Contd. of page 7)

Trade name: CWS WERTLACK® Cowirant Brilliant

Conditions to avoid Keep away from heat sources, sparks and open flames. **Incompatible materials:** strong oxidizing agents **Hazardous decomposition products:** In case of fire may be liberated: Smoke, Carbon monoxide and carbon dioxide.

11 Toxicological information

Information on toxicological effects

Acute toxicity:

LD/LC50 values that are relevant for classification:

The quoted data are literature values and/or manufacturer/supplier data.

Specific symptoms in biological assay:

on the skin: Repeated exposure may cause skin dryness or cracking.

on the eye: Splashes of solvent may cause irritation to the eye and reversible damage.

Sensitization: No sensitizing effects known.

Additional toxicological information: Carcinogenic.

Carcinogenic categories

IARC (International Agency for Research on Cancer)

1330-20-7 xylene (mix)

27253-31-2 Neodecansäure, Cobaltsalz

98-83-9 2-phenylpropene

NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

Aspiration hazard Due to the viscosity (see section 9), classification as an aspiration hazard is omitted.

12 Ecological information

Toxicity

Biodegradation

Aquatic toxicity: There are no statements/information available of the preparation.

Persistence and degradability

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics</th>OECD 301F Manometric Respirometry Test80 % (28d)Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics</td>

80 % (28d)

(Contd. on page 9)

3

2B

2B



acc. to OSHA HCS

Printing date Jan 25, 2023

Trade name: CWS WERTLACK® Cowirant Brilliant

Behavior in environmental systems:

Bioaccumulative potential

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Partition Coefficient log Pow 5-6.7 (n-octanol/water)

Mobility in soil No further relevant information available.

Results of PBT and vPvB assessment

This product does not contain relevant substances that have been assessed as persistent, bioaccumulative and toxic (PBT) or as very persistent and very bioaccumulative (vPvB). **PBT:** Not applicable. **vPvB:** Not applicable.

Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods

Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

UN-Number		
ADR, IMDG, IATA	UN1263	
UN proper shipping name		
DOT	Paint	
ADR	1263 PAINT	
IMDG, IATA	PAINT	
Transport hazard class(es)		
DOT		
Class	3 Flammable liquids	
Label	3	

Reviewed on Jan 25, 2023

DÖRKEN

(Contd. of page 8)

acc. to OSHA HCS

Printing date Jan 25, 2023

Reviewed on Jan 25, 2023

DÖRKEN

Trade name: CWS WERTLACK® Cowirant Brilliant

	(Contd. of page
ADR	
Class	3 (F1) Flammable liquids
Label	3
IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group	
DOT, ADR, IMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code):	
EMS Number:	F-E,S-E
Stowage Category	A
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 60 L
	On cargo aircraft only: 220 L
ADR	
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
Dementer	Maximum net quantity per outer packaging: 1000 ml
Remarks:	When using receptacles with a capacity of at most 450 litr the transport is not subject to the regulations/specification
	of the ADR. However, it is recommended to note then in t
	shipping documents:
MDC	> TRANSPORT AFTER SUBSECTION 2.2.3.1.5 ADR <
IMDG	51
Limited quantities (LQ)	5L Code: E1
Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml

acc. to OSHA HCS

Printing date Jan 25, 2023

Trade name: CWS WERTLACK® Cowirant Brilliant

(Conto, or page 10)	
cked in	Remarks:

UN "Model Regulation":

UN 1263 PAINT, 3, III, (D/E)

15 Regulatory information Safety, health and environmental regulations/legislation specific for the substance or mixture Sara Section 355 (extremely hazardous substances): None of the ingredient is listed. Section 313 (Specific toxic chemical listings): 1330-20-7 xylene (mix) 27253-31-2 Neodecansäure, Cobaltsalz 111-90-0 2-(2-ethoxyethoxy)ethanol 85-44-9 phthalic anhydride 112-34-5 2-(2-Butoxyethoxy)ethanol **TSCA (Toxic Substances Control Act):** 34590-94-8 Dipropylene glycol monomethyl ether ACTIVE 1330-20-7 xylene (mix) ACTIVE 623-40-5 2-Pentanone oxime ACTIVE 27253-30-1 Lithiumneodecanoat ACTIVE 127519-17-9 A mixture of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-ACTIVE dimethyl-ethyl)-4-hydroxyphenyl]propionates 53988-05-9 calcium isononanoate ACTIVE 27253-31-2 Neodecansäure, Cobaltsalz ACTIVE 111-90-0 2-(2-ethoxyethoxy)ethanol ACTIVE 26896-20-8 2-ethyl-2,5-dimethylhexanoic acid ACTIVE 85-44-9 phthalic anhydride ACTIVE 108-65-6 2-Methoxy-1-methylethyl acetate ACTIVE 112-34-5 2-(2-Butoxyethoxy)ethanol ACTIVE 4075-81-4 calcium dipropionate ACTIVE 84268-33-7 Benzenepropanoic acid, 3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxy-, ACTIVE methyl ester 98-83-9 2-phenylpropene ACTIVE **Hazardous Air Pollutants** 1330-20-7 xylene (mix) 27253-31-2 Neodecansäure, Cobaltsalz 85-44-9 phthalic anhydride

(Contd. on page 12)

....



Reviewed on Jan 25, 2023

(Contd. of page 10)

acc. to OSHA HCS

Printing date Jan 25, 2023

Proposition 65

Trade name: CWS WERTLACK® Cowirant Brilliant

(Contd. of page 11)

Τ

A4

A4

Reviewed on Jan 25, 2023

Chemicals known to cause cancer:

98-83-9 2-phenylpropene

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

Carcinogenic categories

EPA (Environmental Protection Agency)

1330-20-7 xylene (mix)

TLV (Threshold Limit Value)

1330-20-7 xylene (mix)

85-44-9 phthalic anhydride

MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). **Hazard pictograms**



Signal word Warning Hazard statements Flammable liquid and vapor. Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 13)

DÖRKEN

acc. to OSHA HCS

Printing date Jan 25, 2023

Reviewed on Jan 25, 2023

DÖRKEN

(Contd. of page 12)

Trade name: CWS WERTLACK® Cowirant Brilliant

National regulations:

Information about limitation of use:

Observe employment restrictions concerning young persons.

Observe employment restrictions for expectant or nursing mothers.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The given conditions of work of the user extract themselves from our knowledge and control. The product/the preparation may be used without written permission for no other use, than the mentioned intended purpose. The user is responsible for the observance of all necessary legal instructions.

This Safety Data Sheet replaces all previous versions. With the newest version in each case, the preceding Safety Data Sheets are set out of strength.

For further information please consult the "Technical Data Sheet". Misuse may cause damage to health and environment.

Contact:

Date of preparation / last revision Jan 25, 2023 Abbreviations and acronyms: Flammable Liquids 3: Flammable liquids – Category 3 Sources

- Verordnung 1907/2006/EG (REACH-Verordnung)

- Verordnung 1272/2008/EG (CLP-Verordnung)

* Data compared to the previous version altered.