Page 1/14

DÖRKEN

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.07.2023

Version number 03-00 (replaces version 02-00)

Revision: 31.07.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1 Product identifier Trade name: DELTA® Kombigrund 7.03

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Coating agent

Uses advised against

This product is not suitable for uses other than those specified in the "Use of the substance/mixture". If your particular manner of use is not listed, please contact the creator of this safety data sheet.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Dörken Coatings GmbH & Co. KG Wetterstr. 58 58313 Herdecke Germany www.doerkencoatings.de

Phone: +49 2330 63 243 Fax: +49 2330 63 100 243

Further information obtainable from: msds.coatings@doerken.de

1.4 Emergency telephone number:

Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 31.07.2023

Version number 03-00 (replaces version 02-00)

Revision: 31.07.2023

Trade name: DELTA® Kombigrund 7.03

Hererd nietes	(Contd. of page
Hazard pictog	jrains
<u>く (で) く (</u>	
GHS02 GHS	507
Signal word V	Varning
Hazard-deterr	nining components of labelling:
	, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Hazard staten	nents
H226 Flamma	ble liquid and vapour.
•	se drowsiness or dizziness.
Precautionary	/ statements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing mist/vapours/spray.
P303+P361+P	353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P312	Call a POISON CENTER/doctor if you feel unwell.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Additional inf	ormation:
EUH066 Repe	ated exposure may cause skin dryness or cracking.
	ains phthalic anhydride, turpentine (mix.), 3-lodo-2-propynylbutylcarbamate. May produce ar jic reaction.
EUH211 Warn mist.	ing! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or
2.3 Other haz	ards
Vapours of the	product are heavier than air and may accumulate below ground level, in pits, channels and
basements in I	higher concentration.
•	orm explosive mixtures with air.
	lation: Higher doses may lead to a narcotic effect.
	BT and vPvB assessment
PBT: Not appl	icable.
vPvB: Not app	Nicable

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2%	25-<50%
Reg.nr.: 01-2119463258-33-xxxx		
	Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336, EUH066	
	(Co	ntd on page 3)



according to 1907/2006/EC, Article 31

Printing date 31.07.2023

Version number 03-00 (replaces version 02-00)

Revision: 31.07.2023

Trade name: DELTA® Kombigrund 7.03

	(Co	ontd. of page 2)
CAS: 13463-67-7 EINECS: 236-675-5 Reg.nr.: 01-2119489379-17-xxxx	Titanium dioxide Carc. 2, H351	10-<25%
EC number: 918-481-9 Reg.nr.: 01-2119457273-39-xxxx	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics Asp. Tox. 1, H304, EUH066	3-<5%
CAS: 85-44-9 EINECS: 201-607-5 Reg.nr.: 01-2119457017-41-xxxx	phthalic anhydride Resp. Sens. 1, H334; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	0.1-<0.3%
CAS: 8006-64-2 EINECS: 232-350-7	turpentine (mix.) Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	0.1-<0.3%
CAS: 55406-53-6 EINECS: 259-627-5	3-lodo-2-propynylbutylcarbamate Acute Tox. 3, H331; STOT RE 1, H372; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Acute Tox. 4, H302; Skin Sens. 1, H317	0.1-<0.3%

Additional information:

All hydrocarbons used comply with note P (less than 0.1% benzene) of the CLP regulation. For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

In all cases of doubt, or when symptoms persist, seek medical advice.

Soiled, soaked clothes immediately take off.

Never give anything by mouth to an unconscious person.

After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Wash with plenty of soap and water.

In case of skin reactions consult a physician. Do not scratch.

After eye contact:

Remove contact lenses. Keep eye lids open and rinse plentifully for at least 10 minutes with clean running water. Subsequently consult an ophthalmologist.

In case of troubles or persistent symptoms, consult an opthalmologist.

After swallowing:

Rinse out mouth and then drink plenty of water.

Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Printing date 31.07.2023

Version number 03-00 (replaces version 02-00)

Revision: 31.07.2023

(Contd. of page 3)

Trade name: DELTA® Kombigrund 7.03

Headache, dizziness, numbness, sickness/nausea, tiredness, stunning effect, dry skin, allergic reactions.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Extinguishing powder, foam, carbon dioxide. Use fire extinguishing methods suitable to surrounding conditions. **For safety reasons unsuitable extinguishing agents:** Water with full jet

5.2 Special hazards arising from the substance or mixture

Flammable liquid and vapour.

Can form explosive gas-air mixtures.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Fire will produce dangerous decomposition products like dense, black smoke, carbon dioxide (CO₂), carbon monoxide (CO) and nitrogen oxides (NOx). Inhalation may cause serious health damage. Under certain fire conditions, traces of other toxic gases cannot be excluded.

5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device. Wear fully protective suit.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away. Keep away from ignition sources and ensure a well-ventilated room. Do not inhale fumes. Avoid contact with skin and eyes.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Printing date 31.07.2023

Version number 03-00 (replaces version 02-00)

Revision: 31.07.2023

(Contd. of page 4)

Trade name: DELTA® Kombigrund 7.03

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid the formation of ignitible and explosion- hazardous solution vapours.

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Material can become charged elektrostatically. Anti-static clothing including shoes are recommended. Avoid contact with skin and eyes as well as inhalation of vapours.

Avoid the handling of incompatible substances and mixtures. Incompatible substances: see section 10.5

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Use explosion-proof apparatus / fittings and spark-proof tools.

Handle only outside or in explosion protected rooms.

Fumes can combine with air to form an explosive mixture.

7.2 Conditions for safe storage, including any incompatibilities Storage:

Requirements to be met by storerooms and receptacles:

Make sure spills can be contained, e.g. in sump pallets.

Protect from frost, heat and direct sunlight. Keep tightly closed, cool and dry.

Information about storage in one common storage facility:

Note the rules for common storage in accordance with TRGS 510 - "Storage of hazardous substances in transportable containers".

Store away from foodstuffs.

Further information about storage conditions: None.

Storage class: 3

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

8006-64-2 turpentine (mix.)

MAK (Germany) Long-term value: 28 mg/m³, 5 ppm

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls Provide good ventilation and/or an exhaust system in the work area.

Appropriate engineering controls

Ensure a good ventilation. This can be achieved by local exhaustion or general exhaust air.

Individual protection measures, such as personal protective equipment General protective and hygienic measures:

Wash hands before breaks and at the end of work.

(Contd. on page 6)

according to 1907/2006/EC, Article 31

Printing date 31.07.2023

Version number 03-00 (replaces version 02-00)

Revision: 31.07.2023

(Contd. of page 5)

DÖRKEN

Trade name: DELTA® Kombigrund 7.03

Avoid contact with the eyes and skin. Immediately remove all soiled and contaminated clothing Do not inhale gases / fumes / aerosols. Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection.

Respiratory protection:

Use always breathing protection with splashing medium. Use combination filter type A(-P2) according to EN 141.

Hand protection

Work with gloves. Gloves must be inspected for damage before use. Defective or damaged gloves must not be used. Gloves must satisfy the specifications of EC directive 89/686/EWG and standard EN 374.

Material of gloves

Nitrile rubber

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection

Wear protective goggles to protect against splashing. Have eye wash bottle or eye rinse ready at work place. Professional Cooperative Rules - BGR 192 Use of eye and face protection

Body protection: Solvent resistant protective clothing

9.1 Information on basic physical and c	hemical properties	
General Information		
Physical state	Fluid	
Colour:	Different according to colouring	
Odour:	Weak after aliphatic hydrocarbons	
Odour threshold:	For mixtures not applicable.	
Melting point/Freezing point:	Not security-related.	
Boiling point or initial boiling point and	boiling	
range	160 °C	
Flammability	Flammable.	
Lower and upper explosion limit		
Lower:	0.6 Vol %	
Upper:	7 Vol %	
Flash point:	36 °C	



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.07.2023

Version number 03-00 (replaces version 02-00)

Revision: 31.07.2023

Trade name: DELTA® Kombigrund 7.03

Auto-ignition temperature:	>200 °C
Decomposition temperature:	For mixtures not applicable.
pH Mineseitu	Mixture is non-soluble (in water).
Viscosity:	< 60 s (20°C / ISO 2431 / 6 mm)
0 - 1	> 20,5 mm²/s (40°C)
Solubility	
water:	Not miscible or difficult to mix.
polar solvents:	Not miscible or difficult to mix.
non-polar solvents:	Fully miscible.
Partition coefficient n-octanol/water (log value)	
Vapour pressure at 20 °C:	6.6 hPa
Density and/or relative density	
Density at 20 °C:	1.28-1.3 g/cm³
Vapour density	Not applicable.
9.2 Other information	
Appearance:	
Form:	Fluid
mportant information on protection of health a	ind
environment, and on safety.	
gnition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
Change in condition	
Softening point/range	
Oxidising properties	The product is flammable, although not oxidising.
Evaporation rate	For mixtures not applicable.
nformation with regard to physical hazard	
classes	
Explosives	Void
Flammable gases	Void
Fidifiliable gases	
Aaraaala	
	Void
Oxidising gases	Void
Oxidising gases Gases under pressure	Void Void
Oxidising gases Gases under pressure Flammable liquids	Void Void Flammable liquid and vapour.
Oxidising gases Gases under pressure Flammable liquids Flammable solids	Void Void Flammable liquid and vapour. Void
Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures	Void Void Flammable liquid and vapour. Void Void
Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids	Void Void Flammable liquid and vapour. Void
Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures	Void Void Flammable liquid and vapour. Void Void
Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids	Void Void Flammable liquid and vapour. Void Void Void
Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures	Void Void Flammable liquid and vapour. Void Void Void Void
Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammab	Void Void Flammable liquid and vapour. Void Void Void Void Void
Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammab gases in contact with water	Void Void Flammable liquid and vapour. Void Void Void Void Void Ie Void
Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammab	Void Void Flammable liquid and vapour. Void Void Void Void Void



according to 1907/2006/EC, Article 31

Printing date 31.07.2023

Version number 03-00 (replaces version 02-00)

Revision: 31.07.2023

Trade name: DELTA® Kombigrund 7.03

		(Contd. of page 7)
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

10.1 Reactivity Vapours can form explosive mixtures with air.

10.2 Chemical stability Product is stable under normal storage conditions.

10.3 Possibility of hazardous reactions

No dangerous reactions known.

No dangerous reactions are known.

10.4 Conditions to avoid Keep away from heat sources, sparks and open flames.

10.5 Incompatible materials: strong oxidizing agents

10.6 Hazardous decomposition products:

In case of fire arise: smoke and carbon oxides. Under certain fire conditions tracks of other toxic products can not be excluded.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

The quoted data are literature values and/or manufacturer/supplier data.

8006-64-2 turpentine (mix.)

Oral	LD_{50}	500 mg/kg (ATE)
Dermal	LD₅₀	1,100 mg/kg (ATE)
Inhalative		11 mg/l (ATE)

55406-53-6 3-lodo-2-propynylbutylcarbamate

Oral	LD₅₀	300-500 mg/kg (rat)
Dermal	LD₅₀	>2,000 mg/kg (rat)
Inhalative	LC₅₀ / 4 h	0.5 mg/l (ATE)

Skin corrosion/irritation

Based on available data, the classification criteria are not met. Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation

Splashes of solvent may cause irritation to the eye and reversible damage. Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met. Germ cell mutagenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met.

(Contd. on page 9)

⁻ DE/EN



according to 1907/2006/EC, Article 31

Printing date 31.07.2023

Version number 03-00 (replaces version 02-00)

Revision: 31.07.2023

(Contd. of page 8)

Trade name: DELTA® Kombigrund 7.03

STOT-single exposure May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard

Due to the viscosity (see section 9), classification as an aspiration hazard is omitted. Based on available data, the classification criteria are not met.

General notes:

Inhalation of solvent concentrations in excess of the OEL or MAK limit values can lead to health damage such as irritation of the mucous membranes and respiratory tract, damage to the kidneys and liver, and impairment of the central nervous system. Symptoms: headaches, dizziness, fatigue, muscle weakness, narcotic effect and, in exceptional cases, loss of consciousness. Prolonged or repeated contact with the product impairs the skin's natural lipid replenishment and causes the skin to dry out. The product can enter the body through the skin. Splashes of solvent may cause irritation to the eye and reversible damage.

Additional toxicological information:

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

The product is not classified as carcinogenic, mutagenic or toxic to reproduction (CMR properties).

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1	Toxicity
------	----------

Aquatic toxicity:			
55406-53-6 3-lodo-2-propynylbutylcarbamate			
EC₅₀ / 48 h	0.47 mg/l (daphnia) (OECD 202)		
EC₅₀ / 72 h	0.049 mg/l (Pseudokirchneriella s	subcapitata) (OECD 201)	
LC₅₀ / 96 h (dynamic)	0.145 mg/l (Oncorhynchus mykis	s (rainbow trout))	
NOEC / 21 d	10 mg/l (daphnia) (OECD 211)		
NOEC / 28 d	0.014 mg/l (Pimephales promelas	s (fathead minnow)) (OECD 210)	
12.2 Persistence and degradability			
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics			
Biodegradation		80 % (28d)	
		readily biodegradable	
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics			
OECD 301F Manome	tric Respirometry Test	80 % (28d)	
		readily biodegradable	
55406-53-6 3-lodo-2-propynylbutylcarbamate			
OECD 307 Aerobic A	nd Anaerobic Transformation Soil	0.03-0.04 d (soil microorganisms)	
OECD 308 Simulation	Biodegradation Aqu Sed System	1-1.2 d (degradation half-life)	
		•	(Contd. on page 1

DE/EN



according to 1907/2006/EC, Article 31

Printing date 31.07.2023

Version number 03-00 (replaces version 02-00)

Revision: 31.07.2023

(Contd. of page 9)

Trade name: DELTA® Kombigrund 7.03

12.3 Bioaccumulative potential

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Partition Coefficient log Pow 5-6.7 (n-octanol/water)

55406-53-6 3-lodo-2-propynylbutylcarbamate

Partition Coefficient log Pow 2.8 (n-octanol/water) (OECD 117)

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

This product does not contain relevant substances that have been assessed as persistent, bioaccumulative and toxic (PBT) or as very persistent and very bioaccumulative (vPvB). **PBT:** Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects No further relevant information available.

Behaviour in sewage processing plants:		
55406-53-6 3-lodo-2-propynylbutylcarbamate		
OECD 302B Zahn-Wellens Test	>70 % (activated sludge organisms)	
OECD 303A Activated Sludge Units	100 % (activated sludge organisms)	
EC ₂₀ / 3 h	8.2 mg/l (activated sludge organisms) (OECD 209)	
EC₅₀ / 3 h	8.2 mg/l (activated sludge organisms) (OECD 209)	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

European waste catalogue 08 01 11* waste paint and varnish containing organic solvents or other hazardous substances HP3 Flammable HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity HP14 Ecotoxic

SECTION 14: Transport information

14.1 UN number or ID number ADR, IMDG, IATA

UN1263

(Contd. on page 11)

DE/EN -



according to 1907/2006/EC, Article 31

Printing date 31.07.2023

Version number 03-00 (replaces version 02-00)

Revision: 31.07.2023

Trade name: DELTA® Kombigrund 7.03

	(Contd. of page 1
14.2 UN proper shipping name ADR	1263 PAINT
IMDG, IATA	PAINT
14.3 Transport hazard class(es)	
ADR	
Class	3 (F1) Flammable liquids.
Label	3
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	111
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number:	F-E, <u>S-E</u>
Stowage Category	A
14.7 Maritime transport in bulk according to IMC	
instruments	Not applicable.
Transport/Additional information: ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code IMDG	D/E
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
	(Contd. on page 1



according to 1907/2006/EC, Article 31

Printing date 31.07.2023

Version number 03-00 (replaces version 02-00)

Revision: 31.07.2023

(Contd. of page 11)

Trade name: DELTA® Kombigrund 7.03

UN "Model Regulation":

UN 1263 PAINT, 3, III, (D/E)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations:

Information about limitation of use:

Observe employment restrictions concerning young persons.

Observe employment restrictions for expectant or nursing mothers.

Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

Labelling according to Regulation (EC) No 2004/42

VOC limit 2010 for category i (SB): 500 g/l. This product contains max 500 g/l VOCs.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The given conditions of work of the user extract themselves from our knowledge and control. The product/the preparation may be used without written permission for no other use, than the mentioned intended purpose. The user is responsible for the observance of all necessary legal instructions.

Page 13/14



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.07.2023

Version number 03-00 (replaces version 02-00)

Revision: 31.07.2023

Trade name: DELTA® Kombigrund 7.03

(Contd. of page 12)

This Safety Data Sheet replaces all previous versions. With the newest version in each case, the preceding Safety Data Sheets are set out of strength.

For further information please consult the "Technical Data Sheet". Misuse may cause damage to health and environment.

Labelling according to regulation (EC) No 528/2012 Additional information:

Contains coating protective agent.

Contains phthalic anhydride, turpentine (mix.), 3-lodo-2-propynylbutylcarbamate. May produce an allergic reaction.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. **Relevant phrases**

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

Flammable liquids	On basis of test data
Specific target organ toxicity (single exposure)	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
Date of previous version: 13.01.2022	
Version number of previous version: 02-00	
Abbreviations and acronyms:	
Flam. Liq. 3: Flammable liquids – Category 3	
Acute Tox. 4: Acute toxicity – Category 4	
Acute Tox. 3: Acute toxicity – Category 3	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Dam. 1: Serious eye damage/eye irritation - Category	y 1
Eye Irrit. 2: Serious eye damage/eye irritation - Category 2	2
Resp. Sens. 1: Respiratory sensitisation - Category 1	
Skin Sens. 1: Skin sensitisation – Category 1	
	(Contd. on page 1

Page 14/14

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.07.2023

Version number 03-00 (replaces version 02-00)

Revision: 31.07.2023

Trade name: DELTA® Kombigrund 7.03

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* Data compared to the previous version altered.

(Contd. of page 13)

DE/EN

