

according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 04-02 Revision: 02.03.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: LUCITE® 800 HousePaint

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Coating agent

Uses advised against

This product is not suitable for uses other than those specified in the "Use of the substance/mixture". If your particular manner of use is not listed, please contact the creator of this safety data sheet.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Dörken Coatings GmbH & Co. KG

Wetterstr. 58 58313 Herdecke

Germany

www.doerkencoatings.de

Phone: +49 2330 63 243 Fax: +49 2330 63 100 243

Further information obtainable from: msds.coatings@doerken.de

1.4 Emergency telephone number:

Emergency CONTACT (24-Hour-Number):

GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



Signal word Warning

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 04-02 Revision: 02.03.2023

Trade name: LUCITE® 800 HousePaint

(Contd. of page 1)

Hazard-determining components of labelling:

2-methyl-2H-isothiazol-3-one 2-octyl-2H-isothiazol-3-one

mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

1,2-benzisothiazol-3(2H)-one

diuron

Hazard statements

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 13463-67-7 EINECS: 236-675-5 Reg.nr.: 01-2119489379-17-xxxx	Titanium dioxide Carc. 2, H351	10-25%
CAS: 57-55-6 EINECS: 200-338-0 Reg.nr.: 01-2119456809-23-xxxx	Propylene glycol substance with a Community workplace exposure limit	<5%
		(Contd. on page :

(Contd. on page 3)

GB



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 04-02 Revision: 02.03.2023

Trade name: LUCITE® 800 HousePaint

	T	(Contd. of page
CAS: 2634-33-5	1,2-benzisothiazol-3(2H)-one	≥0-<0.025%
EINECS: 220-120-9 Reg.nr.: 01-2120761540-60-xxxx	Acute Tox. 2, H330; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute	
	Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317	
	Specific concentration limit: Skin Sens. 1; H317: C≥ 0.05 %	
CAS: 2682-20-4	2-methyl-2H-isothiazol-3-one	≥0.0015-<0.025%
EINECS: 220-239-6	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute	
Reg.nr.: 01-2120764690-50-xxxx		
3	H318; Aquatic Acute 1, H400 (M=10); Aquatic	
	Chronic 1, H410 (M=1); Skin Sens. 1A, H317,	
	EUH071	
	Specific concentration limit:	
	Skin Sens. 1A; H317: C≥ 0.0015 %	
CAS: 26530-20-1	2-octyl-2H-isothiazol-3-one	≥0.0025-<0.025%
EINECS: 247-761-7	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute	
	Tox. 2, H330; Skin Corr. 1, H314; Eye Dam. 1,	
	H318; Aquatic Acute 1, H400 (M=100); Aquatic	
	Chronic 1, H410 (M=100); Skin Sens. 1A, H317,	
	EUH071	
	ATE: LD₅o oral: 125 mg/kg	
	LD₅₀ dermal: 311 mg/kg	
	LC₅₀ / 4 h inhalative: 0.27 mg/l	
	Specific concentration limit:	
	Skin Sens. 1A; H317: C≥ 0.0015 %	
CAS: 3811-73-2	pyridine-2-thiol 1-oxide, sodium salt	≥0.0025-<0.025%
EINECS: 223-296-5	Acute Tox. 3, H311; Acute Tox. 3, H331; STOT RE	
Reg.nr.: 01-2119493385-28-xxxx		
	Chronic 2, H411; Acute Tox. 4, H302; Skin Irrit. 2,	
	H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 55965-84-9	mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one	≥0.00025-<0.0015°
Reg.nr.: 01-2120764691-48-xxxx	and 2-methyl-2H-isothiazol-3-one (3:1)	
	Acute Tox. 3, H301; Acute Tox. 2, H310; Acute	
	Tox. 2, H330; Skin Corr. 1C, H314; Eye Dam. 1,	
	H318; Aquatic Acute 1, H400 (M=100); Aquatic	
	Chronic 1, H410 (M=100); Skin Sens. 1A, H317	
	Specific concentration limits:	
	Skin Corr. 1C; H314:C ≥ 0.6 %	
	Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 %	
	Eye Dam. 1; H318: C ≥ 0.6 %	
	Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %	



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 04-02 Revision: 02.03.2023

Trade name: LUCITE® 800 HousePaint

(Contd. of page 3)

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

In all cases of doubt, or when symptoms persist, seek medical advice.

Soiled, soaked clothes immediately take off.

Never give anything by mouth to an unconscious person.

After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

Take off immediately all contaminated clothing and wash it before reuse.

After eye contact:

Remove contact lenses. Keep eye lids open and rinse plentifully for at least 10 minutes with clean running water. Subsequently consult an ophthalmologist.

In case of troubles or persistent symptoms, consult an opthalmologist.

After swallowing:

Rinse mouth thoroughly with water.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Extinguishing powder, foam, carbon dioxide.

Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Fire will produce dangerous decomposition products like dense, black smoke, carbon dioxide (CO₂), carbon monoxide (CO) and nitrogen oxides (NOx). Inhalation may cause serious health damage.

Under certain fire conditions, traces of other toxic gases cannot be excluded.

5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 04-02 Revision: 02.03.2023

Trade name: LUCITE® 800 HousePaint

(Contd. of page 4)

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Avoid contact with skin and eyes.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Keep contaminated washing water and dispose of appropriately.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid prolonged, intensive skin contact and contact with the eyes.

Avoid the handling of incompatible substances and mixtures. Incompatible substances: see section 10.5

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Make sure spills can be contained, e.g. in sump pallets.

Protect from frost, heat and direct sunlight. Keep tightly closed, cool and dry.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions: None.

Storage class: 12

7.3 Specific end use(s) No further relevant information available.

GB



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 04-02 Revision: 02.03.2023

Trade name: LUCITE® 800 HousePaint

(Contd. of page 5)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

57-55-6 Propylene glycol

WEL (Great Britain) Long-term value: 474* 10** mg/m³, 150* ppm *total vapour and particulates **particulates

Regulatory information WEL (Great Britain): EH40/2020

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls Provide good ventilation and/or an exhaust system in the work area.

Appropriate engineering controls

Ensure a good ventilation. This can be achieved by local exhaustion or general exhaust air.

Individual protection measures, such as personal protective equipment General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing

Do not eat, drink, smoke or sniff while working.

Use skin protection cream for skin protection.

Respiratory protection:

Use always breathing protection with splashing medium.

Use combination filter type A(-P2) according to EN 141.

Hand protection

Work with gloves. Gloves must be inspected for damage before use. Defective or damaged gloves must not be used. Gloves must satisfy the specifications of EC directive 89/686/EWG and standard EN 374. It is recommended to use long gloves to minimize contact by splashing.

Material of gloves

Nitrile rubber

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection

Wear protective goggles to protect against splashing.

Have eye wash bottle or eye rinse ready at work place.

Body protection: Impervious protective clothing

GE



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 04-02 Revision: 02.03.2023

Trade name: LUCITE® 800 HousePaint

(Contd. of page 6)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state Fluid

Colour: Different according to colouring

Odour:Weak after glycol ethersOdour threshold:For mixtures not applicable.

Melting point/Freezing point: Not security-related.

Boiling point or initial boiling point and boiling

range 100 °C (7732-18-5 water)

Flammability Not applicable.

Lower and upper explosion limit

Lower:Not determined.Upper:Not determined.Flash point:Not applicable.Ignition temperature:Not applicable.

Decomposition temperature: For mixtures not applicable.

pH at 20 °C 8.4-9.2

Viscosity: Not security-related.

Solubility

water: Miscible / waterdilutable.

polar solvents: Partly miscible.

non-polar solvents:

Partition coefficient n-octanol/water (log value)

Vapour pressure at 20 °C:

Not miscible or difficult to mix.

For mixtures not applicable.

23 hPa (7732-18-5 water)

Density and/or relative density

Density at 20 °C: 1.22-1.45 g/cm³ Vapour density Not applicable.

9.2 Other information

Appearance:

Form: Fluid

Important information on protection of health and

environment, and on safety.

Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

Change in condition Softening point/range

Oxidising properties In its condition as supplied, the product is neither

flammable nor oxidising.

Evaporation rate For mixtures not applicable.

Information with regard to physical hazard

classes

Explosives Void Flammable gases Void

(Contd. on page 8)



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 04-02 Revision: 02.03.2023

Trade name: LUCITE® 800 HousePaint

(Contd. of page 7)

Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable	
gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions are known.

No further relevant information available.

10.2 Chemical stability Product is stable under normal storage conditions.

10.3 Possibility of hazardous reactions

No dangerous reactions known.

No dangerous reactions are known.

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: strong oxidizing agents

10.6 Hazardous decomposition products:

In case of fire arise: smoke and carbon oxides. Under certain fire conditions tracks of other toxic products can not be excluded.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

The quoted data are literature values and/or manufacturer/supplier data.

Skin corrosion/irritation May cause irritations.

Serious eye damage/irritation May cause irritations.

Respiratory or skin sensitisation May cause an allergic skin reaction.

(Contd. on page 9)



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 04-02 Revision: 02.03.2023

Trade name: LUCITE® 800 HousePaint

(Contd. of page 8)

Aspiration hazard

The mixture contains no or only small amounts of materials which are classified as an aspiration hazard. It can therefore be assumed that the mixture is not an aspiration hazard.

Additional toxicological information:

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

The product is not classified as carcinogenic, mutagenic or toxic to reproduction (CMR properties).

11.2 Information on other hazards

Endocrine disrupting properties

330-54-1 diuron

List II

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Harmful to aquatic life with long lasting effects.

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

12.5 Results of PBT and vPvB assessment

This product does not contain relevant substances that have been assessed as persistent, bioaccumulative and toxic (PBT) or as very persistent and very bioaccumulative (vPvB).

PBT: Not applicable. **vPvB:** Not applicable.

12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects

Other information:

This product contains the following priority substance in accordance with Annex X of the EU Water Directive 2000/60/EC:

330-54-1 Diuron

General notes: Do not allow product to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

GE



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 04-02 Revision: 02.03.2023

Trade name: LUCITE® 800 HousePaint

(Contd. of page 9)

14.1 UN number or ID number		
ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk according	g to IMO	
instruments	Not applicable.	
UN "Model Regulation":	Void	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

National regulations:

Information about limitation of use:

Observe employment restrictions concerning young persons.

Observe employment restrictions for expectant or nursing mothers.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The given conditions of work of the user extract themselves from our knowledge and control. The product/the preparation may be used without written permission for no other use, than the mentioned intended purpose. The user is responsible for the observance of all necessary legal instructions.

This Safety Data Sheet replaces all previous versions. With the newest version in each case, the preceding Safety Data Sheets are set out of strength.

For further information please consult the "Technical Data Sheet".

(Contd. on page 11)

DÖRKEN

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 04-02 Revision: 02.03.2023

Trade name: LUCITE® 800 HousePaint

(Contd. of page 10)

Misuse may cause damage to health and environment.

Additional information:

Contains protective agent for products in storage and coating protective agent.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

it piliases
Toxic if swallowed.
Harmful if swallowed.
Fatal in contact with skin.
Toxic in contact with skin.
Causes severe skin burns and eye damage.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.
Causes serious eye irritation.
Fatal if inhaled.
Toxic if inhaled.
Suspected of causing cancer.
Causes damage to organs through prolonged or repeated exposure.
Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects. H410

Toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

Abbreviations and acronyms:

Acute Tox. 3: Acute toxicity - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Acute Tox. 2: Acute toxicity - Category 2 Skin Corr. 1: Skin corrosion/irritation - Category 1 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Corr. 1C: Skin corrosion/irritation - Category 1C Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A

Carc. 2: Carcinogenicity - Category 2

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

Sources

- Regulation 1907/2006/EC (UK REACH-Regulation)
- Regulation 1272/2008/EC (GB CLP-Regulation)
- * Data compared to the previous version altered.