Page 1/12



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2024

Version number 06-01 (replaces version 06-00)

Revision: 23.01.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: LUCITE® 112 Primer

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Coating agent

Uses advised against

This product is not suitable for uses other than those specified in the "Use of the substance/mixture". If your particular manner of use is not listed, please contact the creator of this safety data sheet.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Dörken Coatings GmbH & Co. KG Wetterstr. 58 58313 Herdecke Germany www.doerkencoatings.de

Phone: +49 2330 63 243 Fax: +49 2330 63 100 243

Further information obtainable from: msds.coatings@doerken.de

1.4 Emergency telephone number:

Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 The product is not classified, according to the CLP regulation.

2.2 Label elements
Labelling according to Regulation (EC) No 1272/2008 Void
Hazard pictograms Void
Signal word Void
Hazard statements Void
Precautionary statements
P280 Wear protective gloves.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
Additional information:
EUH208 Contains mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.
EUH210 Safety data sheet available on request.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

(Contd. on page 2)

Page 2/12



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2024

Version number 06-01 (replaces version 06-00)

Revision: 23.01.2024

(Contd. of page 1)

Trade name: LUCITE® 112 Primer

2.3 Other hazards Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable.

*

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

CAS: 13463-67-7	Titanium dioxide	10-25%
EINECS: 236-675-5	Carc. 2, H351	-
Reg.nr.: 01-2119489379-17-xxxx		
CAS: 34590-94-8	Dipropylene glycol monomethyl ether	<5%
EINECS: 252-104-2	substance with a Community workplace exposure	
Reg.nr.: 01-2119450011-60-xxxx		
CAS: 111-76-2	2-butoxyethanol	<2.5%
EINECS: 203-905-0	Acute Tox. 3, H331; Acute Tox. 4, H302; Skin Irrit.	
Reg.nr.: 01-2119475108-36-xxxx		
	ATE: LD₅o oral: 1,200 mg/kg	
	LC₅₀ / 4 h inhalative: 3 mg/l	
CAS: 67-64-1	acetone	<2.5%
EINECS: 200-662-2	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3,	
0		
CAS: 77-99-6	propylidynetrimethanol	<0.25%
EINECS: 201-074-9	Repr. 2, H361fd	
Reg.nr.: 01-2119486799-10-xxxx		0.00005 0.00450
CAS: 55965-84-9	mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	≥0.00025-<0.0015%
Reg.III 01-2120704091-46-XXXX	Acute Tox. 3, H301; Acute Tox. 2, H310; Acute	-
	Tox. 2, H330; Skin Corr. 1C, H314; Eye Dam. 1,	
	H318; Aquatic Acute 1, H400 (M=100); Aquatic	
	Chronic 1, H410 (M=100); Skin Sens. 1A, H317,	
	EUH071	
	Specific concentration limits:	
	Skin Corr. 1C; H314:C ≥ 0.6 %	
	Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 %	
	Eye Dam. 1; H318: C ≥ 0.6 %	
	Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 %	
	Skin Sens. 1A; H317: C ≥ 0.0015 %	

(Contd. on page 3)



according to 1907/2006/EC, Article 31

Printing date 23.01.2024

Version number 06-01 (replaces version 06-00)

Revision: 23.01.2024

(Contd. of page 2)

Trade name: LUCITE® 112 Primer

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

In all cases of doubt, or when symptoms persist, seek medical advice.

Soiled, soaked clothes immediately take off.

Never give anything by mouth to an unconscious person.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact:

Wash with plenty of soap and water.

In case of skin reactions consult a physician. Do not scratch.

After eye contact:

Remove contact lenses. Keep eye lids open and rinse plentifully for at least 10 minutes with clean running water. Subsequently consult an ophthalmologist.

In case of troubles or persistent symptoms, consult an opthalmologist.

After swallowing:

Rinse out mouth and then drink plenty of water.

Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Extinguishing powder, foam, carbon dioxide.

Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Fire will produce dangerous decomposition products like dense, black smoke, carbon dioxide (CO₂), carbon monoxide (CO) and nitrogen oxides (NOx). Inhalation may cause serious health damage. Under certain fire conditions, traces of other toxic gases cannot be excluded.

5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device. Wear fully protective suit.

Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

(Contd. on page 4)

DE/EN



according to 1907/2006/EC, Article 31

Printing date 23.01.2024

Version number 06-01 (replaces version 06-00)

Revision: 23.01.2024

Trade name: LUCITE® 112 Primer

(Contd. of page 3)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away. Avoid contact with skin and eyes.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Keep contaminated washing water and dispose of appropriately.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid prolonged, intensive skin contact and contact with the eyes. Avoid the handling of incompatible substances and mixtures. Incompatible substances: see section 10.5

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities Storage:

Requirements to be met by storerooms and receptacles:

Make sure spills can be contained, e.g. in sump pallets.

Protect from frost, heat and direct sunlight. Keep tightly closed, cool and dry.

Information about storage in one common storage facility:

Note the rules for common storage in accordance with TRGS 510 - "Storage of hazardous substances in transportable containers".

Store away from foodstuffs.

Further information about storage conditions: None.

Storage class: 12

7.3 Specific end use(s) No further relevant information available.

(Contd. on page 5)

DE/EN



according to 1907/2006/EC, Article 31

Printing date 23.01.2024

Version number 06-01 (replaces version 06-00)

(Contd. of page 4)

Trade name: LUCITE® 112 Primer

8.1 Control para	meters
Ingredients with	Imit values that require monitoring at the workplace:
57-55-6 Propyle	ne glycol
	als Dampf und Aerosol;vgl.Abschn.IIb und Xc
-	opylene glycol monomethyl ether
AGW (Germany)	Long-term value: 310 mg/m³, 50 ppm 1(I);DFG, EU, 11
IOELV (EU)	Long-term value: 308 mg/m³, 50 ppm Skin
111-76-2 2-buto	kyethanol
AGW (Germany)	Long-term value: 49 mg/m³, 10 ppm 2(I);EU, DFG; H, Y
IOELV (EU)	Short-term value: 246 mg/m³, 50 ppm Long-term value: 98 mg/m³, 20 ppm Skin
67-64-1 acetone	
AGW (Germany)	Long-term value: 1200 mg/m³, 500 ppm 2(I);AGS, DFG, EU, Y
IOELV (EU)	Long-term value: 1210 mg/m³, 500 ppm
55965-84-9 mixt	ure of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3
MAK (Germany)	Long-term value: 0.2E mg/m³ vgl.Abschn.Xc
Regulatory info	
AGW (Germany)	
IOELV (EU): (EU	·
-	i biological limit values:
111-76-2 2-buto	-
BGW (Germany)	150 mg/g Kreatinin Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende, bei Langzeitexposition: an Schichtende nach mehreren vorangegangenen Schichten Parameter: Butoxyessigsäure (nach Hydrolyse)
67-64-1 acetone	
BGW (Germany)	50 mg/l Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: Aceton
Regulatory info	rmation BGW (Germany): TRGS 903

(Contd. on page 6)

⁻ DE/EN

Page 6/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2024

Version number 06-01 (replaces version 06-00)

Revision: 23.01.2024

(Contd. of page 5)

DÖRKEN[®]

Trade name: LUCITE® 112 Primer

Appropriate engineering controls

Ensure a good ventilation. This can be achieved by local exhaustion or general exhaust air.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing

Do not eat, drink, smoke or sniff while working.

Use skin protection cream for skin protection.

Respiratory protection:

Breathing protection is always required when spraying. Use combination filter A2(-P2) according to EN 14387.

Hand protection

Material of gloves

Nitrile rubber

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection

Wear protective goggles to protect against splashing. Professional Cooperative Rules - BGR 192 Use of eye and face protection

Body protection: Impervious protective clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical	properties
General Information	
Physical state	Fluid
Colour:	Different according to colouring
Odour:	Ammonia-like
Odour threshold:	For mixtures not applicable.
Melting point/Freezing point:	Not security-related.
Boiling point or initial boiling point and boiling	
range	100 °C (H₂O, 7732-18-5 water)
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2024

Version number 06-01 (replaces version 06-00)

Revision: 23.01.2024

Trade name: LUCITE® 112 Primer

Elash noint:	Not applicable	
Flash point:	Not applicable.	
Auto-ignition temperature:	Not applicable.	
Decomposition temperature:	For mixtures not applicable.	
pH at 20 °C	8-9	
Viscosity:	Not security-related.	
Solubility		
water:	Miscible / waterdilutable.	
polar solvents:	Partly miscible.	
non-polar solvents:	Not miscible or difficult to mix.	
Partition coefficient n-octanol/water (log value)	For mixtures not applicable.	
Vapour pressure at 20 °C:	23 hPa (H₂O, 7732-18-5 water)	
Density and/or relative density		
Density at 20 °C:	1.21-1.41 g/cm³	
Vapour density	Not applicable.	
9.2 Other information		
Appearance:		
Form:	Fluid	
Important information on protection of health and		
environment, and on safety.	•	
Ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product does not present an explosion hazard.	
Change in condition	roudel does not present an explosion hazard.	
Softening point/range		
	In its condition on sumplied the product is poither.	
Oxidising properties	In its condition as supplied, the product is neither	
Evaporation rate	flammable nor oxidising. For mixtures not applicable.	
-		
Information with regard to physical hazard		
classes		
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flammable		
gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
-		
Organic peroxides	Void	



according to 1907/2006/EC, Article 31

Printing date 23.01.2024

Version number 06-01 (replaces version 06-00)

Revision: 23.01.2024

Trade name: LUCITE® 112 Primer

		(Contd. of page 7)
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability Product is stable under normal storage conditions.

10.3 Possibility of hazardous reactions

No dangerous reactions known.

No dangerous reactions are known.

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: strong oxidizing agents

10.6 Hazardous decomposition products:

In case of fire arise: smoke and carbon oxides. Under certain fire conditions tracks of other toxic products can not be excluded.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met. LD/LC50 values relevant for classification:

The quoted data are literature values and/or manufacturer/supplier data.

Oral	LD_{50}	1,200 mg/kg (ATE)
Inhalative	LC₅₀ / 4 h	3 mg/l (ATE)

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met. Germ cell mutagenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard

The mixture contains no or only small amounts of materials which are classified as an aspiration hazard. It can therefore be assumed that the mixture is not an aspiration hazard. Based on available data, the classification criteria are not met.

(Contd. on page 9)

- DF/FN

according to 1907/2006/EC, Article 31

Printing date 23.01.2024

Version number 06-01 (replaces version 06-00)

Revision: 23.01.2024

(Contd. of page 8)

List II; III

List II

List II

Trade name: LUCITE® 112 Primer

Additional toxicological information:

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

The product is not classified as carcinogenic, mutagenic or toxic to reproduction (CMR properties).

11.2 Information on other hazards

Endocrine disrupting properties

556-67-2 octamethylcyclotetrasiloxane

540-97-6 Dodecamethylcyclohexasiloxane

541-02-6 Decamethylcyclopentasiloxane

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

111-76-2 2-butoxyethanol

EC₅₀ / 24 h 1,800 mg/l (Daphnia magna (big water flea))

EC₅₀ / 72 h 911 mg/l (Selenastrum capricornutum)

LC₅₀ / 96 h 1,700 mg/l (Oncorhynchus mykiss (rainbow trout))

>100 mg/l (Lepomis macrochirus (bluegill))

12.2 Persistence and degradability

111-76-2 2-butoxyethanol

OECD 301B CO₂-Evolution Test (Sturm Test) 90.4 % (28d)

readily biodegradable

12.3 Bioaccumulative potential

111-76-2 2-butoxyethanol

Partition Coefficient log Pow 0.81 (n-octanol/water) (25 °C; pH 7)

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

This product does not contain relevant substances that have been assessed as persistent, bioaccumulative and toxic (PBT) or as very persistent and very bioaccumulative (vPvB). **PBT:** Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 10)



Page 10/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2024

Version number 06-01 (replaces version 06-00)

Revision: 23.01.2024

Trade name: LUCITE® 112 Primer

Must be specially treated adhering to official regulations.

European waste catalogue

08 01 12 waste paint and varnish other than those mentioned in 08 01 11

14.1 UN number or ID number		
ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name		
ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk according	g to IMO	
instruments	Not applicable.	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Regulation (EC) No 273/2004 on drug precursors

67-64-1 acetone

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

67-64-1 acetone

(Contd. on page 11)



3

3



(Contd. of page 9)



according to 1907/2006/EC, Article 31

Printing date 23.01.2024

Version number 06-01 (replaces version 06-00)

Revision: 23.01.2024

(Contd. of page 10)

DÖRKEN[®]

Trade name: LUCITE® 112 Primer

National regulations:

Information about limitation of use:

Observe employment restrictions concerning young persons.

Observe employment restrictions for expectant or nursing mothers.

Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

Labelling according to Regulation (EC) No 2004/42

VOC limit according to 2004/42/EC for category d (WB) and maximum VOC content: see lid.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The given conditions of work of the user extract themselves from our knowledge and control. The product/the preparation may be used without written permission for no other use, than the mentioned intended purpose. The user is responsible for the observance of all necessary legal instructions.

This Safety Data Sheet replaces all previous versions. With the newest version in each case, the preceding Safety Data Sheets are set out of strength.

For further information please consult the "Technical Data Sheet". Misuse may cause damage to health and environment.

Labelling according to regulation (EC) No 528/2012

Additional information:

Contains protective agent for products in storage.

Contains mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

Safety data sheet available on request.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H310 Fatal in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H331 Toxic if inhaled.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

(Contd. on page 12)

Page 12/12



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2024

Version number 06-01 (replaces version 06-00)

Revision: 23.01.2024

Trade name: LUCITE® 112 Primer

	(Contd. of page 11)
EUH066 Repeated exposure may cause skin dryness or cracking.	
EUH071 Corrosive to the respiratory tract.	
Date of previous version: 02.03.2023	
Version number of previous version: 06-00	
Abbreviations and acronyms:	
Flam. Liq. 2: Flammable liquids – Category 2	
Acute Tox. 4: Acute toxicity – Category 4	
Acute Tox. 2: Acute toxicity – Category 2	
Acute Tox. 3: Acute toxicity – Category 3	
Skin Corr. 1C: Skin corrosion/irritation – Category 1C	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Dam. 1: Serious eye damage/eye irritation – Category 1	
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	
Skin Sens. 1A: Skin sensitisation – Category 1A	
Carc. 2: Carcinogenicity – Category 2	
Repr. 2: Reproductive toxicity – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1	
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1	
* Data compared to the previous version altered.	
	DE/EN