

according to 1907/2006/EC, Article 31

Printing date 28.02.2024 Version number 03-01 (replaces version 03-00) Revision: 28.02.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: LUCITE® 844 SilicoTec

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Coating agent

Uses advised against

This product is not suitable for uses other than those specified in the "Use of the substance/mixture". If your particular manner of use is not listed, please contact the creator of this safety data sheet.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Dörken Coatings GmbH & Co. KG

Wetterstr. 58 58313 Herdecke

Germany

www.doerkencoatings.de

Phone: +49 2330 63 243 Fax: +49 2330 63 100 243

Further information obtainable from: msds.coatings@doerken.de

1.4 Emergency telephone number:

Emergency CONTACT (24-Hour-Number):

GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



Signal word Warning

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 28.02.2024 Version number 03-01 (replaces version 03-00) Revision: 28.02.2024

Trade name: LUCITE® 844 SilicoTec

(Contd. of page 1)

Hazard-determining components of labelling:

2-methyl-2H-isothiazol-3-one 1,2-benzisothiazol-3(2H)-one

mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

2-octyl-2H-isothiazol-3-one

pyrithione zinc Terbutryn

Hazard statements

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:				
CAS: 13463-67-7 EINECS: 236-675-5 Reg.nr.: 01-2119489379-17-xxxx	Titanium dioxide Carc. 2, H351	≥1-≤10%		
CAS: 2682-20-4 EINECS: 220-239-6 Reg.nr.: 01-2120764690-50-xxxx	2-methyl-2H-isothiazol-3-one Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C≥ 0.0015 %	≥0.0015-<0.025%		
CAS: 886-50-0 EINECS: 212-950-5	Terbutryn Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Acute Tox. 4, H302; Skin Sens. 1B, H317 Specific concentration limit: Skin Sens. 1B; H317: C≥ 3 %	≥0.0025-<0.025%		

(Contd. on page 3)



according to 1907/2006/EC, Article 31

Printing date 28.02.2024 Version number 03-01 (replaces version 03-00) Revision: 28.02.2024

Trade name: LUCITE® 844 SilicoTec

		(Contd. of page 2)
CAS: 13463-41-7 EINECS: 236-671-3 Reg.nr.: 01-2119511196-46-xxxx	pyrithione zinc Acute Tox. 3, H301; Acute Tox. 2, H330; Repr. 1A, H360D; STOT RE 1, H372; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=1000); Aquatic Chronic 1, H410 (M=10) ATE: LD ₅₀ oral: 221 mg/kg LC ₅₀ / 4 h inhalative: 0.14 mg/l	≥0.0025-<0.025%
CAS: 26530-20-1 EINECS: 247-761-7	2-octyl-2H-isothiazol-3-one Ācute Tox. $\overline{3}$, $\overline{H301}$; Acute Tox. $\overline{3}$, $\overline{H311}$; Acute Tox. $\overline{2}$, $\overline{H330}$; Skin Corr. $\overline{1}$, $\overline{H314}$; Eye Dam. $\overline{1}$, $\overline{H318}$; Aquatic Acute $\overline{1}$, $\overline{H400}$ (M=100); Aquatic Chronic $\overline{1}$, $\overline{H410}$ (M=100); Skin Sens. $\overline{1}$ A, $\overline{H317}$, $\overline{1}$ EUH071 ATE: $\overline{1}$ ED ₅₀ oral: $\overline{1}$ 25 mg/kg $\overline{1}$ B ₅₀ dermal: $\overline{1}$ 311 mg/kg $\overline{1}$ B ₅₀ dermal: $\overline{1}$ 311 mg/kg $\overline{1}$ B ₅₀ / $\overline{1}$ 4 h inhalative: $\overline{1}$ 5.27 mg/l Specific concentration limit: $\overline{1}$ 5kin Sens. $\overline{1}$ 4; $\overline{1}$ 317: $\overline{1}$ 5 0.0015 %	≥0.0025-<0.025%
CAS: 55965-84-9 Reg.nr.: 01-2120764691-48-xxxx	mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317, EUH071 Specific concentration limits: Skin Corr. 1C; H314:C \geq 0.6 % Skin Irrit. 2; H315: 0.06 % \leq C < 0.6 % Eye Dam. 1; H318: C \geq 0.6 % Eye Irrit. 2; H319: 0.06 % \leq C < 0.6 % Skin Sens. 1A; H317: C \geq 0.0015 %	≥0.00025-<0.0015%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

In all cases of doubt, or when symptoms persist, seek medical advice.

Soiled, soaked clothes immediately take off.

Never give anything by mouth to an unconscious person.

After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly. If skin irritation or rash occurs: Get medical advice/attention.

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Printing date 28.02.2024 Version number 03-01 (replaces version 03-00) Revision: 28.02.2024

Trade name: LUCITE® 844 SilicoTec

(Contd. of page 3)

Take off immediately all contaminated clothing and wash it before reuse.

After eye contact:

Remove contact lenses. Keep eye lids open and rinse plentifully for at least 10 minutes with clean running water. Subsequently consult an ophthalmologist.

In case of troubles or persistent symptoms, consult an opthalmologist.

After swallowing:

Rinse mouth thoroughly with water.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Extinguishing powder, foam, carbon dioxide.

Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Fire will produce dangerous decomposition products like dense, black smoke, carbon dioxide (CO_2) , carbon monoxide (CO) and nitrogen oxides (NOx). Inhalation may cause serious health damage.

Under certain fire conditions, traces of other toxic gases cannot be excluded.

5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Avoid contact with skin and eyes.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Keep contaminated washing water and dispose of appropriately.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Printing date 28.02.2024 Version number 03-01 (replaces version 03-00) Revision: 28.02.2024

Trade name: LUCITE® 844 SilicoTec

(Contd. of page 4)

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid prolonged, intensive skin contact and contact with the eyes.

Avoid the handling of incompatible substances and mixtures. Incompatible substances: see section 10.5

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Make sure spills can be contained, e.g. in sump pallets.

Protect from frost, heat and direct sunlight. Keep tightly closed, cool and dry.

Information about storage in one common storage facility:

Note the rules for common storage in accordance with TRGS 510 - "Storage of hazardous substances in transportable containers".

Store away from foodstuffs.

Further information about storage conditions: None.

Storage class: 12

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

13463-41-7 pyrithione zinc

MAK (Germany) vgl. Abschn.llb

55965-84-9 mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

MAK (Germany) Long-term value: 0.2E mg/m³

vgl.Abschn.Xc

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls Provide good ventilation and/or an exhaust system in the work area.

Appropriate engineering controls

Ensure a good ventilation. This can be achieved by local exhaustion or general exhaust air.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

(Contd. on page 6)



according to 1907/2006/EC, Article 31

Printing date 28.02.2024 Version number 03-01 (replaces version 03-00) Revision: 28.02.2024

Trade name: LUCITE® 844 SilicoTec

(Contd. of page 5)

Immediately remove all soiled and contaminated clothing

Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection.

Respiratory protection:

Breathing protection is always required when spraying. Use combination filter A2(-P2) according to EN 14387.

Hand protection

Work with gloves. Gloves must be inspected for damage before use. Defective or damaged gloves must not be used. Gloves must satisfy the specifications of EC directive 89/686/EWG and standard EN 374. It is recommended to use long gloves to minimize contact by splashing.

Material of gloves

Nitrile rubber

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection

Wear protective goggles to protect against splashing.

Have eye wash bottle or eye rinse ready at work place.

Professional Cooperative Rules - BGR 192 Use of eye and face protection

Body protection: Impervious protective clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state Fluid

Colour: Different according to colouring

Odour: Weak after glycol ethers
Odour threshold: For mixtures not applicable.

Melting point/Freezing point: Not security-related.

Boiling point or initial boiling point and boiling

range 100 °C (7732-18-5 water)

Flammability Not applicable.

Lower and upper explosion limit

Lower:Not determined.Upper:Not determined.Flash point:Not applicable.Auto-ignition temperature:Not applicable.

(Contd. on page 7)



according to 1907/2006/EC, Article 31

Printing date 28.02.2024 Version number 03-01 (replaces version 03-00) Revision: 28.02.2024

Trade name: LUCITE® 844 SilicoTec

(Contd. of page 6)

Decomposition temperature: For mixtures not applicable.

pH at 20 °C

Viscosity: Not security-related.

Solubility

Miscible / waterdilutable. water:

polar solvents: Partly miscible.

non-polar solvents: Not miscible or difficult to mix. Partition coefficient n-octanol/water (log value) For mixtures not applicable. Vapour pressure at 20 °C: 23 hPa (7732-18-5 water)

Density and/or relative density

Density at 20 °C: 1.49-1.57 g/cm³ Vapour density Not applicable.

9.2 Other information

Appearance:

Form: Fluid

Important information on protection of health and

environment, and on safety.

Ignition temperature: Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

Change in condition Softening point/range

Oxidising properties In its condition as supplied, the product is neither

flammable nor oxidising.

For mixtures not applicable. **Evaporation rate**

Information with regard to physical hazard

classes **Explosives**

Void Flammable gases Void **Aerosols** Void Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void

Self-reactive substances and mixtures Void **Pyrophoric liquids** Void Pyrophoric solids Void Self-heating substances and mixtures Void

Substances and mixtures, which emit flammable

Void gases in contact with water **Oxidising liquids** Void Void **Oxidising solids** Organic peroxides Void Corrosive to metals Void

(Contd. on page 8)



according to 1907/2006/EC, Article 31

Printing date 28.02.2024 Version number 03-01 (replaces version 03-00) Revision: 28.02.2024

Trade name: LUCITE® 844 SilicoTec

(Contd. of page 7)

Desensitised explosives

Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability Product is stable under normal storage conditions.
- 10.3 Possibility of hazardous reactions

No dangerous reactions known.

No dangerous reactions are known.

- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: strong oxidizing agents
- 10.6 Hazardous decomposition products:

In case of fire arise: smoke and carbon oxides. Under certain fire conditions tracks of other toxic products can not be excluded.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification: No further relevant information available.

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard

The mixture contains no or only small amounts of materials which are classified as an aspiration hazard. It can therefore be assumed that the mixture is not an aspiration hazard.

Based on available data, the classification criteria are not met.

Additional toxicological information:

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

The product is not classified as carcinogenic, mutagenic or toxic to reproduction (CMR properties).

(Contd. on page 9)

DE/EN



according to 1907/2006/EC, Article 31

Printing date 28.02.2024 Version number 03-01 (replaces version 03-00) Revision: 28.02.2024

Trade name: LUCITE® 844 SilicoTec

(Contd. of page 8)

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Harmful to aquatic life with long lasting effects.

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

12.5 Results of PBT and vPvB assessment

This product does not contain relevant substances that have been assessed as persistent, bioaccumulative and toxic (PBT) or as very persistent and very bioaccumulative (vPvB).

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Other information:

This product contains the following priority substance in accordance with Annex X of the EU Water Directive 2000/60/EC:

886-50-0 Terbutryn

General notes: Do not allow product to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

European waste catalogue		
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	
HP14	Ecotoxic	

DE/EN -

(Contd. on page 10)



according to 1907/2006/EC, Article 31

Printing date 28.02.2024 Version number 03-01 (replaces version 03-00) Revision: 28.02.2024

Trade name: LUCITE® 844 SilicoTec

(Contd. of page 9)

14.1 UN number or ID number		
ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name		
ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk according	j to IMO	
instruments	Not applicable.	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

(Contd. on page 11)



according to 1907/2006/EC, Article 31

Printing date 28.02.2024 Version number 03-01 (replaces version 03-00) Revision: 28.02.2024

Trade name: LUCITE® 844 SilicoTec

(Contd. of page 10)

National regulations:

Information about limitation of use:

Observe employment restrictions concerning young persons.

Observe employment restrictions for expectant or nursing mothers.

Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

Labelling according to Regulation (EC) No 2004/42

VOC limit 2010 for category c (WB): 40 g/l. This product contains max 40 g/l VOCs.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The given conditions of work of the user extract themselves from our knowledge and control. The product/the preparation may be used without written permission for no other use, than the mentioned intended purpose. The user is responsible for the observance of all necessary legal instructions.

This Safety Data Sheet replaces all previous versions. With the newest version in each case, the preceding Safety Data Sheets are set out of strength.

For further information please consult the "Technical Data Sheet".

Misuse may cause damage to health and environment.

Labelling according to regulation (EC) No 528/2012

Additional information:

Contains protective agent for products in storage and coating protective agent.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Relevant phrases

Toxic if swallowed.
Harmful if swallowed.
Fatal in contact with skin.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H330 Fatal if inhaled.

H351 Suspected of causing cancer. H360D May damage the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

Classification according t	o Regulation (EC) No 1272/2008
----------------------------	----------------	------------------

Skin sensitisation
Hazardous to the aquatic environment - long-term
(chronic) aquatic hazard

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

(Contd. on page 12)



according to 1907/2006/EC, Article 31

Printing date 28.02.2024 Version number 03-01 (replaces version 03-00) Revision: 28.02.2024

Trade name: LUCITE® 844 SilicoTec

(Contd. of page 11)

Date of previous version: 08.03.2021

Version number of previous version: 03-00

Abbreviations and acronyms: Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 2: Acute toxicity – Category 2
Skin Corr. 1: Skin corrosion/irritation – Category 1
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Corr. 1C: Skin corrosion/irritation – Category 1C
Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1A: Skin sensitisation – Category 1A
Skin Sens. 1B: Skin sensitisation – Category 1B
Carc. 2: Carcinogenicity – Category 2
Repr. 1A: Reproductive toxicity – Category 1A

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.

DE/EN -