Page 1/12



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.03.2024

Version number 03-03 (replaces version 03-02)

Revision: 13.03.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: DELTA® Buntlack Aqua GL

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Coating agent

Uses advised against

This product is not suitable for uses other than those specified in the "Use of the substance/mixture". If your particular manner of use is not listed, please contact the creator of this safety data sheet.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Dörken Coatings GmbH & Co. KG Wetterstr. 58 58313 Herdecke Germany www.doerkencoatings.de

Phone: +49 2330 63 243 Fax: +49 2330 63 100 243

Further information obtainable from: msds.coatings@doerken.de

1.4 Emergency telephone number:

Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 The product is not classified, according to the CLP regulation.

2.2 Label elements
Labelling according to Regulation (EC) No 1272/2008 Void
Hazard pictograms Void
Signal word Void
Hazard statements Void
Precautionary statements
P280 Wear protective gloves.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
Additional information:
EUH208 Contains mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
EUH210 Safety data sheet available on request.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

(Contd. on page 2)

Page 2/12



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.03.2024

Version number 03-03 (replaces version 03-02)

Revision: 13.03.2024

(Contd. of page 1)

Trade name: DELTA® Buntlack Aqua GL

2.3 Other hazards Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable.

*

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

CAS: 13463-67-7	Titanium dioxide	10-25%
EINECS: 236-675-5 Reg.nr.: 01-2119489379-17-xxxx	Carc. 2, H351	10-25%
CAS: 111-76-2	2-butoxyethanol	<5%
EINECS: 203-905-0 Reg.nr.: 01-2119475108-36-xxxx		
	ATE: LD₅₀ oral: 1,200 mg/kg LC₅₀ / 4 h inhalative: 3 mg/l	
CAS: 112-34-5 EINECS: 203-961-6 Reg.nr.: 01-2119475104-44-xxxx	2-(2-Butoxyethoxy)ethanol Eye Irrit. 2, H319	≥1-<2.5%
CAS: 77-99-6 EINECS: 201-074-9 Reg.nr.: 01-2119486799-10-xxxx	propylidynetrimethanol Repr. 2, H361fd	<0.25%
CAS: 2634-33-5 EINECS: 220-120-9 Reg.nr.: 01-2120761540-60-xxxx	1,2-benzisothiazol-3(2H)-one Acute Tox. 2, H330; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1; H317: C≥ 0.05 %	≥0.025-<0.05%
CAS: 55965-84-9 Reg.nr.: 01-2120764691-48-xxxx	mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317, EUH071 Specific concentration limits: Skin Corr. 1C; H314:C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %	≥0.00025-<0.00159



according to 1907/2006/EC, Article 31

Printing date 13.03.2024

Version number 03-03 (replaces version 03-02)

Revision: 13.03.2024

(Contd. of page 2)

Trade name: DELTA® Buntlack Aqua GL

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

In all cases of doubt, or when symptoms persist, seek medical advice. Soiled, soaked clothes immediately take off. Never give anything by mouth to an unconscious person. **After inhalation:** Supply fresh air; consult doctor in case of complaints. **After skin contact:** Wash with plenty of soap and water. In case of skin reactions consult a physician. Do not scratch. **After eye contact:** Remove contact lenses. Keep eye lids open and rinse plentifully for at least 10 minutes with clean running water. Subsequently consult an ophthalmologist. In case of troubles or persistent symptoms, consult an opthalmologist. **After swallowing:**

Rinse out mouth and then drink plenty of water. Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Extinguishing powder, foam, carbon dioxide. Use fire extinguishing methods suitable to surrounding conditions. **For safety reasons unsuitable extinguishing agents:** Water with full jet

5.2 Special hazards arising from the substance or mixture

Fire will produce dangerous decomposition products like dense, black smoke, carbon dioxide (CO₂), carbon monoxide (CO) and nitrogen oxides (NOx). Inhalation may cause serious health damage. Under certain fire conditions, traces of other toxic gases cannot be excluded.

5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device. Wear fully protective suit.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

DE/EN



according to 1907/2006/EC, Article 31

Printing date 13.03.2024

Version number 03-03 (replaces version 03-02)

Revision: 13.03.2024

Trade name: DELTA® Buntlack Aqua GL

(Contd. of page 3)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away. Avoid contact with skin and eyes.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Keep contaminated washing water and dispose of appropriately.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid prolonged, intensive skin contact and contact with the eyes. Avoid the handling of incompatible substances and mixtures. Incompatible substances: see section 10.5

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities Storage:

Requirements to be met by storerooms and receptacles:

Make sure spills can be contained, e.g. in sump pallets.

Protect from frost, heat and direct sunlight. Keep tightly closed, cool and dry.

Information about storage in one common storage facility:

Note the rules for common storage in accordance with TRGS 510 - "Storage of hazardous substances in transportable containers".

Store away from foodstuffs.

Further information about storage conditions: None.

Storage class: 12

7.3 Specific end use(s) No further relevant information available.

(Contd. on page 5)

DE/EN

Page 5/12



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.03.2024

Version number 03-03 (replaces version 03-02)

Revision: 13.03.2024

(Contd. of page 4)

Trade name: DELTA® Buntlack Aqua GL

	(Conto. of page 4)
SECTION 8: Ex	posure controls/personal protection
8.1 Control parame	eters
Ingredients with lin	mit values that require monitoring at the workplace:
111-76-2 2-butoxye	ethanol
	.ong-term value: 49 mg/m³, 10 ppm 2(I);EU, DFG; H, Y
Lo	Short-term value: 246 mg/m³, 50 ppm .ong-term value: 98 mg/m³, 20 ppm Skin
57-55-6 Propylene	glycol
MAK (Germany) al	Is Dampf und Aerosol;vgl.Abschn.IIb und Xc
112-34-5 2-(2-Buto	oxyethoxy)ethanol
	.ong-term value: 67 mg/m³, 10 ppm .5(I);EU, DFG, Y, 11
	Short-term value: 101.2 mg/m³, 15 ppm .ong-term value: 67.5 mg/m³, 10 ppm
55965-84-9 mixture	e of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
	.ong-term value: 0.2E mg/m³ /gl.Abschn.Xc
Regulatory informa AGW (Germany): T IOELV (EU): (EU) 2	-RGS 900
Ingredients with bi	iological limit values:
111-76-2 2-butoxye	ethanol
P S	50 mg/g Kreatinin Jntersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende, bei Langzeitexposition: am Schichtende nach mehreren vorangegangenen Schichten Parameter: Butoxyessigsäure (nach Hydrolyse)
	nation BGW (Germany): TRGS 903 ation: The lists valid during the making were used as basis.
Appropriate engine	t rols Provide good ventilation and/or an exhaust system in the work area. Teering controls tilation. This can be achieved by local exhaustion or general exhaust air.
General protective Wash hands before Avoid contact with th Immediately remove Do not eat, drink, sn	ion measures, such as personal protective equipment e and hygienic measures: e breaks and at the end of work. the eyes and skin. e all soiled and contaminated clothing moke or sniff while working. cream for skin protection. (Contd. on page 6)



according to 1907/2006/EC, Article 31

Printing date 13.03.2024

Version number 03-03 (replaces version 03-02)

Revision: 13.03.2024

(Contd. of page 5)

Trade name: DELTA® Buntlack Aqua GL

Respiratory protection:

Breathing protection is always required when spraying. Use combination filter A2(-P2) according to EN 14387.

Hand protection

Material of gloves

Nitrile rubber

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection

Wear protective goggles to protect against splashing. Professional Cooperative Rules - BGR 192 Use of eye and face protection

Body protection: Impervious protective clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chem	ical properties	
General Information		
Physical state	Fluid	
Colour:	Different according to colouring	
Odour:	Ammonia-like	
Odour threshold:	For mixtures not applicable.	
Melting point/Freezing point:	Not security-related.	
Boiling point or initial boiling point and boil	ing	
range	100 °C (7732-18-5 water)	
Flammability	Not applicable.	
Lower and upper explosion limit		
Lower:	Not determined.	
Upper:	Not determined.	
Flash point:	Not applicable.	
Auto-ignition temperature:	Not applicable.	
Decomposition temperature:	For mixtures not applicable.	
pH at 20 °C	7-9	
Viscosity:	Not security-related.	
Solubility	,	
water:	Miscible / waterdilutable.	
polar solvents:	Partly miscible.	
non-polar solvents:	Not miscible or difficult to mix.	
		(Contd. on page 7)



according to 1907/2006/EC, Article 31

Printing date 13.03.2024

Version number 03-03 (replaces version 03-02)

Revision: 13.03.2024

Trade name: DELTA® Buntlack Aqua GL

	(Contd. of page
Partition coefficient n-octanol/water (log value)	For mixtures not applicable.
Vapour pressure at 20 °C:	23 hPa (7732-18-5 water)
Density and/or relative density	
Density at 20 °C:	1.01-1.27 g/cm³
Vapour density	Not applicable.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health and	d diama di seconda di s
environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Change in condition	
Softening point/range	
Oxidising properties	In its condition as supplied, the product is neither
	flammable nor oxidising.
Evaporation rate	For mixtures not applicable.
Information with regard to physical hazard	
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable	
gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability Product is stable under normal storage conditions.

[–] DE/EN –



according to 1907/2006/EC, Article 31

Printing date 13.03.2024

Version number 03-03 (replaces version 03-02)

Revision: 13.03.2024

(Contd. of page 7)

Trade name: DELTA® Buntlack Aqua GL

10.3 Possibility of hazardous reactions

No dangerous reactions known.

No dangerous reactions are known.

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: strong oxidizing agents

10.6 Hazardous decomposition products:

In case of fire arise: smoke and carbon oxides. Under certain fire conditions tracks of other toxic products can not be excluded.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

111-76-2 2-butoxyethanol

Oral	LD_{50}	1,200 mg/kg (ATE)
Inhalative	LC₅₀ / 4 h	3 mg/l (ATE)

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met. Germ cell mutagenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard

The mixture contains no or only small amounts of materials which are classified as an aspiration hazard. It can therefore be assumed that the mixture is not an aspiration hazard. Based on available data, the classification criteria are not met.

Additional toxicological information:

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

The product is not classified as carcinogenic, mutagenic or toxic to reproduction (CMR properties). **11.2 Information on other hazards**

Endocrine disrupting properties	
556-67-2 octamethylcyclotetrasiloxane	List II; III
541-02-6 Decamethylcyclopentasiloxane	List II
540-97-6 Dodecamethylcyclohexasiloxane	List II

(Contd. on page 9)



according to 1907/2006/EC, Article 31

Printing date 13.03.2024

Version number 03-03 (replaces version 03-02)

Revision: 13.03.2024

Trade name: DELTA® Buntlack Aqua GL

(Contd. of page 8)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

111-76-2 2-butoxyethanol

EC₅₀ / 24 h 1,800 mg/l (Daphnia magna (big water flea))

EC₅₀ / 72 h 911 mg/l (Selenastrum capricornutum)

LC₅₀ / 96 h 1,700 mg/l (Oncorhynchus mykiss (rainbow trout))

>100 mg/l (Lepomis macrochirus (bluegill))

12.2 Persistence and degradability

111-76-2 2-butoxyethanol

OECD 301B CO₂-Evolution Test (Sturm Test) 90.4 % (28d)

readily biodegradable

12.3 Bioaccumulative potential

111-76-2 2-butoxyethanol

Partition Coefficient log Pow 0.81 (n-octanol/water) (25 °C; pH 7)

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

This product does not contain relevant substances that have been assessed as persistent, bioaccumulative and toxic (PBT) or as very persistent and very bioaccumulative (vPvB). **PBT:** Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

European waste catalogue

08 01 12 waste paint and varnish other than those mentioned in 08 01 11

SECTION 14: Transport information

14.1 UN number or ID number

ADR, ADN, IMDG, IATA

Void

(Contd. on page 10)



according to 1907/2006/EC, Article 31

Printing date 13.03.2024

Version number 03-03 (replaces version 03-02)

Revision: 13.03.2024

Trade name: DELTA® Buntlack Aqua GL

		(Contd. of pag
14.2 UN proper shipping name		
ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk according	to IMO	
instruments	Not applicable.	
UN "Model Regulation":	Void	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations:

Information about limitation of use:

Observe employment restrictions concerning young persons.

Observe employment restrictions for expectant or nursing mothers.

Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

(Contd. on page 11)



according to 1907/2006/EC, Article 31

Printing date 13.03.2024

Version number 03-03 (replaces version 03-02)

Revision: 13.03.2024

(Contd. of page 10)

Trade name: DELTA® Buntlack Aqua GL

Labelling according to Regulation (EC) No 2004/42

VOC limit according to 2004/42/EC for category d (WB) and maximum VOC content: see lid. **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The given conditions of work of the user extract themselves from our knowledge and control. The product/the preparation may be used without written permission for no other use, than the mentioned intended purpose. The user is responsible for the observance of all necessary legal instructions.

This Safety Data Sheet replaces all previous versions. With the newest version in each case, the preceding Safety Data Sheets are set out of strength.

For further information please consult the "Technical Data Sheet". Misuse may cause damage to health and environment.

Labelling according to regulation (EC) No 528/2012 Additional information:

Contains protective agent for products in storage.

Contains mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

Safety data sheet available on request.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Relevant phrases

- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H310 Fatal in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H331 Toxic if inhaled.
- H351 Suspected of causing cancer.
- H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- EUH071 Corrosive to the respiratory tract.

Date of previous version: 23.11.2023

Version number of previous version: 03-02

Abbreviations and acronyms:

Acute Tox. 4: Acute toxicity - Category 4

- Acute Tox. 2: Acute toxicity Category 2
- Acute Tox. 3: Acute toxicity Category 3 Skin Corr. 1C: Skin corrosion/irritation – Category 1C

(Contd. on page 12)

Page 12/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.03.2024

Version number 03-03 (replaces version 03-02)

Revision: 13.03.2024

Trade name: DELTA® Buntlack Aqua GL

Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A Carc. 2: Carcinogenicity - Category 2 Repr. 2: Reproductive toxicity - Category 2 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 * Data compared to the previous version altered.

DE/EN

(Contd. of page 11)

DÖRKEN[®]