

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.05.2025 Version number 02-02 (replaces version 02-01) Revision: 07.05.2025

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: CWS WERTLACK® Metallisé

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Coating agent

#### Uses advised against

This product is not suitable for uses other than those specified in the "Use of the substance/mixture". If your particular manner of use is not listed, please contact the creator of this safety data sheet.

#### 1.3 Details of the supplier of the safety data sheet

## Manufacturer/Supplier:

Dörken Coatings GmbH & Co. KG

Wetterstr. 58 58313 Herdecke

Germany

www.doerkencoatings.de

Phone: +49 2330 63 243 Fax: +49 2330 63 100 243

Further information obtainable from: msds.coatings@doerken.de

#### 1.4 Emergency telephone number:

Emergency CONTACT (24-Hour-Number):

GBK GmbH +49 (0)6132-84463

#### **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.05.2025 Version number 02-02 (replaces version 02-01) Revision: 07.05.2025

Trade name: CWS WERTLACK® Metallisé

(Contd. of page 1)

#### **Hazard pictograms**





### Signal word Warning

### Hazard-determining components of labelling:

Hydrocarbons, C9, aromatics

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

1-Methoxy-2-propanol

#### **Hazard statements**

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

#### **Precautionary statements**

P210	Keep away froi	m heat, hot surfa	aces, sparks, open f	lames and other i	gnition sources. No
------	----------------	-------------------	----------------------	-------------------	---------------------

P261 Avoid breathing mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves.

Call a doctor if you feel unwell. P312

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains maleic anhydride. May produce an allergic reaction.

#### 2.3 Other hazards

Vapours of the product are heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Vapours can form explosive mixtures with air.

In case of inhalation: Higher doses may lead to a narcotic effect.

#### Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:			
EC number: 918-668-5	Hydrocarbons, C9, aromatics	≥10-<25%	
Reg.nr.: 01-2119455851-35-xxxx	Alternative CAS number: 64742-95-6		
	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335; STOT SE 3, H336, EUH066		

(Contd. on page 3)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.05.2025 Version number 02-02 (replaces version 02-01) Revision: 07.05.2025

Trade name: CWS WERTLACK® Metallisé

		Contd. of page
EC number: 919-857-5 Reg.nr.: 01-2119463258-33-xxxx	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336, EUH066	≥1-≤10%
CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35-xxxx	1-Methoxy-2-propanol Flam. Liq. 3, H226; STOT SE 3, H336	≥1-≤10%
EC number: 918-481-9 Reg.nr.: 01-2119457273-39-xxxx	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics Asp. Tox. 1, H304, EUH066	≥1-<5%
CAS: 7429-90-5 EINECS: 231-072-3 Reg.nr.: 01-2119529243-45-xxxx	aluminium powder (stabilised) Flam. Sol. 1, H228	≥1-<5%
CAS: 39049-04-2 EINECS: 254-259-1 Reg.nr.: 01-2120770770-52-xxxx	neodecanoic acid, zirconium salt Acute Tox. 4, H302	≥0-<2.5%
CAS: 13463-67-7 EINECS: 236-675-5 Reg.nr.: 01-2119489379-17-xxxx	Titanium dioxide Carc. 2, H351	<1%
CAS: 107-41-5 EINECS: 203-489-0 Reg.nr.: 01-2119539582-35-xxxx	2-methylpentane-2,4-diol Repr. 2, H361d; Skin Irrit. 2, H315; Eye Irrit. 2, H319	≥0-<0.25%
CAS: 108-31-6 EINECS: 203-571-6 Reg.nr.: 01-2119472428-31-xxxx	maleic anhydride Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001	≥0-<0.001 <sup>6</sup>

#### Additional information:

All hydrocarbons used comply with note P (less than 0.1% benzene) of the CLP regulation.

For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

## **General information:**

In all cases of doubt, or when symptoms persist, seek medical advice.

Soiled, soaked clothes immediately take off.

Never give anything by mouth to an unconscious person.

#### After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

#### After skin contact:

Wash with plenty of soap and water.

In case of skin reactions consult a physician. Do not scratch.

(Contd. on page 4)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.05.2025 Version number 02-02 (replaces version 02-01) Revision: 07.05.2025

Trade name: CWS WERTLACK® Metallisé

(Contd. of page 3)

#### After eye contact:

Remove contact lenses. Keep eye lids open and rinse plentifully for at least 10 minutes with clean running water. Subsequently consult an ophthalmologist.

In case of troubles or persistent symptoms, consult an opthalmologist.

#### After swallowing:

Rinse out mouth and then drink plenty of water.

Seek immediate medical advice.

#### 4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Headache, dizziness, numbness, sickness/nausea, tiredness, stunning effect, dry skin, allergic reactions.

## 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

#### Suitable extinguishing agents:

Extinguishing powder, foam, carbon dioxide.

Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

## 5.2 Special hazards arising from the substance or mixture

Flammable liquid and vapour.

Can form explosive gas-air mixtures.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Fire will produce dangerous decomposition products like dense, black smoke, carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO) and nitrogen oxides (NOx). Inhalation may cause serious health damage.

Under certain fire conditions, traces of other toxic gases cannot be excluded.

#### 5.3 Advice for firefighters

### **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

#### Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources and ensure a well-ventilated room. Do not inhale fumes.

Avoid contact with skin and eyes.

(Contd. on page 5)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.05.2025 Version number 02-02 (replaces version 02-01) Revision: 07.05.2025

Trade name: CWS WERTLACK® Metallisé

(Contd. of page 4)

#### 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

#### 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

#### 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Avoid the formation of ignitible and explosion- hazardous solution vapours.

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Material can become charged elektrostatically. Anti-static clothing including shoes are recommended.

Avoid contact with skin and eyes as well as inhalation of vapours.

Avoid the handling of incompatible substances and mixtures. Incompatible substances: see section 10.5

#### Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Use explosion-proof apparatus / fittings and spark-proof tools.

Handle only outside or in explosion protected rooms.

Fumes can combine with air to form an explosive mixture.

## 7.2 Conditions for safe storage, including any incompatibilities

#### Storage:

## Requirements to be met by storerooms and receptacles:

Make sure spills can be contained, e.g. in sump pallets.

Protect from frost, heat and direct sunlight. Keep tightly closed, cool and dry.

### Information about storage in one common storage facility:

Note the rules for common storage in accordance with TRGS 510 - "Storage of hazardous substances in transportable containers".

Store away from foodstuffs.

Further information about storage conditions: None.

Storage class: 3

7.3 Specific end use(s) No further relevant information available.

DE/EN

(Contd. on page 6)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.05.2025 Version number 02-02 (replaces vers

Version number 02-02 (replaces version 02-01) Revision: 07.05.2025

Trade name: CWS WERTLACK® Metallisé

(Contd. of page 5)

### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Hydrocarbons, C9, aromatics		
IOELV (EU) Long-term value: 100 mg/m³, 20 ppm (trimethylbenzole)		
107-98-2 1-Methoxy-2-propanol		
AGW (Germany)	Long-term value: 370 mg/m³, 100 ppm 2(I);DFG, EU, Y	
IOELV (EU)	Short-term value: 568 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Skin	
112945-52-5 Synthetische, amorphe, pyrogene Kieselsäure		
MAK (Germany)	Long-term value: 0.02A mg/m³ vgl. Abschn. V	
107-41-5 2-methylpentane-2,4-diol		
MAK (Germany)	Long-term value: 49 mg/m³, 10 ppm vgl.Abschn.Xc;Dampf und Aerosol	
108-31-6 maleic anhydride		
AGW (Germany)	Long-term value: 0.081 mg/m³, 0.02 ppm 1;=2.5=(I);DFG, Sah, Y, 11	

## **Regulatory information**

IOELV (EU): (EU) 2019/1831 AGW (Germany): TRGS 900

#### Ingredients with biological limit values:

### 107-98-2 1-Methoxy-2-propanol

BGW (Germany) 15 mg/l

Untersuchungsmaterial: Urin

Probennahmezeitpunkt: Expositionsende bzw. Schichtende

Parameter: 1-Methoxypropan-2-ol

Regulatory information BGW (Germany): TRGS 903

Additional information: The lists valid during the making were used as basis.

**8.2 Exposure controls** Provide good ventilation and/or an exhaust system in the work area.

Appropriate engineering controls

Ensure a good ventilation. This can be achieved by local exhaustion or general exhaust air.

## Individual protection measures, such as personal protective equipment General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing

Do not inhale gases / fumes / aerosols.

(Contd. on page 7)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.05.2025 Version number 02-02 (replaces version 02-01) Revision: 07.05.2025

Trade name: CWS WERTLACK® Metallisé

(Contd. of page 6)

Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection.

#### Respiratory protection:

Breathing protection is always required when spraying. Use combination filter A2(-P2) according to EN 14387.

## **Hand protection**

Work with gloves. Gloves must be inspected for damage before use. Defective or damaged gloves must not be used. Gloves must satisfy the specifications of EC directive 89/686/EWG and standard EN 374.

#### **Material of gloves**

Butyl rubber

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### Eye/face protection

Wear protective goggles to protect against splashing. Have eye wash bottle or eye rinse ready at work place.

Professional Cooperative Rules - BGR 192 Use of eye and face protection

Body protection: Solvent resistant protective clothing

## **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

**General Information** 

Physical state Fluid

Colour:Different according to colouringOdour:Strong after aromatic hydrocarbons

Odour threshold: Not applicable for mixtures.

Melting point/Freezing point: Not security-related.

Boiling point or initial boiling point and boiling

boiling point or initial boiling point and boiling

**range** 120 °C (107-98-2 1-Methoxy-2-propanol) Flammability Flammable.

Lower and upper explosion limit

**Lower:** 0.6 Vol % (Hydrocarbons, C9-C11, n-alkanes,

isoalkanes, cyclics, < 2% aromatics)

**Upper:** 13.1 Vol % (107-98-2 1-Methoxy-2-propanol)

Flash point: 37 °C

**Auto-ignition temperature:** >200 °C (Hydrocarbons, C9-C11, n-alkanes,

isoalkanes, cyclics, < 2% aromatics)

(Contd. on page 8)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.05.2025 Version number 02-02 (replaces version 02-01) Revision: 07.05.2025

Trade name: CWS WERTLACK® Metallisé

(Contd. of page 7)

**Decomposition temperature:** For mixtures not applicable.

Mixture is non-soluble (in water). Viscosity: > 90 s (20°C / DIN 53211 / 4 mm)

> 60 s (20°C / ISO 2431 / 6 mm)

 $> 20,5 \text{ mm}^2/\text{s} (40^{\circ}\text{C})$ 

Solubility

water: Not miscible or difficult to mix. polar solvents: Not miscible or difficult to mix.

non-polar solvents: Fully miscible.

Partition coefficient n-octanol/water (log value)

For mixtures not applicable. 13 hPa (107-98-2 1-Methoxy-2-propanol) Vapour pressure at 20 °C:

Density and/or relative density

Density at 20 °C: 1.225-1.245 g/cm<sup>3</sup> Vapour density Not applicable.

9.2 Other information

Appearance:

Form: Fluid

Important information on protection of health and

environment, and on safety.

Ignition temperature: Product is not selfigniting.

**Explosive properties:** Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

Change in condition

Softening point/range

**Oxidising properties** The product is flammable, although not oxidising.

**Evaporation rate** For mixtures not applicable.

Information with regard to physical hazard

classes

**Explosives** Void Flammable gases Void **Aerosols** Void Void Oxidising gases Gases under pressure

Flammable liquids Flammable liquid and vapour.

Flammable solids Void Self-reactive substances and mixtures Void **Pyrophoric liquids** Void Pyrophoric solids Void Self-heating substances and mixtures Void

Substances and mixtures, which emit flammable

gases in contact with water Void **Oxidising liquids** Void **Oxidising solids** Void Organic peroxides Void

(Contd. on page 9)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.05.2025 Version number 02-02 (replaces version 02-01) Revision: 07.05.2025

Trade name: CWS WERTLACK® Metallisé

(Contd. of page 8)

Corrosive to metals Void

Desensitised explosives Void

## **SECTION 10: Stability and reactivity**

- 10.1 Reactivity Vapours can form explosive mixtures with air.
- 10.2 Chemical stability Product is stable under normal storage conditions.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid Keep away from heat sources, sparks and open flames.
- 10.5 Incompatible materials: strong oxidizing agents
- 10.6 Hazardous decomposition products:

In case of fire arise: smoke and carbon oxides. Under certain fire conditions tracks of other toxic products can not be excluded.

## **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

#### LD/LC50 values relevant for classification:

The quoted data are literature values and/or manufacturer/supplier data.

Specific symptoms in biological assay:

#### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

#### Serious eye damage/irritation

Splashes of solvent may cause irritation to the eye and reversible damage.

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Due to the viscosity (see section 9), classification as an aspiration hazard is omitted.

Based on available data, the classification criteria are not met.

#### **General notes:**

Inhalation of solvent concentrations in excess of the OEL or MAK limit values can lead to health damage such as irritation of the mucous membranes and respiratory tract, damage to the kidneys and liver, and impairment of the central nervous system. Symptoms: headaches, dizziness, fatigue, muscle weakness, narcotic effect and, in exceptional cases, loss of consciousness. Prolonged or repeated contact with the product impairs the skin's natural lipid replenishment and causes the skin to dry out. The product can enter

(Contd. on page 10)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.05.2025 Version number 02-02 (replaces version 02-01) Revision: 07.05.2025

Trade name: CWS WERTLACK® Metallisé

(Contd. of page 9)

the body through the skin. Splashes of solvent may cause irritation to the eye and reversible damage.

#### Additional toxicological information:

#### CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

The product is not classified as carcinogenic, mutagenic or toxic to reproduction (CMR properties).

11.2 Information on other hazards

#### **Endocrine disrupting properties**

None of the ingredients is listed.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

## Aquatic toxicity:

Harmful to aquatic life with long lasting effects.

	Hydrocarbons,	C9. aromatics
--	---------------	---------------

EC<sub>50</sub> / 48 h 3.2 mg/l (Daphnia magna (big water flea))

LC<sub>50</sub> / 96 h | 9.2 mg/l (Oncorhynchus mykiss (rainbow trout))

#### 12.2 Persistence and degradability

#### Hydrocarbons, C9, aromatics

OECD 301F Manometric Respirometry Test 78 % /O2 consump (28d)

readily biodegradable

### Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Biodegradation

80 % (28d)

readily biodegradable

### Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

OECD 301F Manometric Respirometry Test 80 % (28d)

readily biodegradable

## 12.3 Bioaccumulative potential

#### Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Partition Coefficient log Pow 5-6.7 (n-octanol/water)

12.4 Mobility in soil No further relevant information available.

#### 12.5 Results of PBT and vPvB assessment

This product does not contain relevant substances that have been assessed as persistent, bioaccumulative and toxic (PBT) or as very persistent and very bioaccumulative (vPvB).

**PBT:** Not applicable.

vPvB: Not applicable.

#### 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

(Contd. on page 11)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.05.2025 Version number 02-02 (replaces version 02-01) Revision: 07.05.2025

Trade name: CWS WERTLACK® Metallisé

(Contd. of page 10)

#### 12.7 Other adverse effects

Other information:

General notes: Do not allow product to reach ground water, water course or sewage system.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

European waste catalogue		
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	
HP3	Flammable	
HP14	Ecotoxic	

## **SECTION 14: Transport information**

14.1 UN number or ID number

ADR, IMDG, IATA UN1263

14.2 UN proper shipping name

ADR 1263 PAINT IMDG, IATA PAINT

## 14.3 Transport hazard class(es)

**ADR** 



Class 3 (F1) Flammable liquids.

Label

IMDG, IATA



Class 3 Flammable liquids.

Label 3

14.4 Packing group

ADR, IMDG, IATA

(Contd. on page 12)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.05.2025 Version number 02-02 (replaces version 02-01) Revision: 07.05.2025

Trade name: CWS WERTLACK® Metallisé

(Contd. of page 11)

14.5 Environmental hazards: Not applicable.

14.6 Special precautions for user Warning: Flammable liquids.

Hazard identification number (Kemler code): **EMS Number:** F-E,S-E **Stowage Category** 

14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

**Transport/Additional information:** 

Limited quantities (LQ) 5L **Excepted quantities (EQ)** Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

**Transport category Tunnel restriction code** D/E

Remarks: When using receptacles with a capacity of at most 450

> litre, the transport is not subject to the regulations/ specifications of the ADR. However, it is recommended

to note then in the shipping documents:

> TRANSPORT AFTER SUBSECTION 2.2.3.1.5 ADR

**IMDG** 

Remarks:

Limited quantities (LQ) 5L

**Excepted quantities (EQ)** Code: E1

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml Not subject to the IMDG provisions when packed in

receptacles not exceeding 30 L capacity.

**UN "Model Regulation":** UN 1263 PAINT, 3, III, (D/E)

## **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 13)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.05.2025 Version number 02-02 (replaces version 02-01) Revision: 07.05.2025

Trade name: CWS WERTLACK® Metallisé

(Contd. of page 12)

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

**REGULATION (EU) 2019/1148** 

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

#### Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

### Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

#### National regulations:

#### Information about limitation of use:

Observe employment restrictions concerning young persons.

Observe employment restrictions for expectant or nursing mothers.

Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

#### Labelling according to Regulation (EC) No 2004/42

VOC limit according to 2004/42/EC for category i (SB) and maximum VOC content: see lid.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The given conditions of work of the user extract themselves from our knowledge and control. The product/the preparation may be used without written permission for no other use, than the mentioned intended purpose. The user is responsible for the observance of all necessary legal instructions.

This Safety Data Sheet replaces all previous versions. With the newest version in each case, the preceding Safety Data Sheets are set out of strength.

For further information please consult the "Technical Data Sheet".

Misuse may cause damage to health and environment.

## Labelling according to regulation (EC) No 528/2012

Additional information: Contains maleic anhydride. May produce an allergic reaction.

## Wording of H and EUH phrases (number and full text)

H226 Flammable liquid and vapour.

H228 Flammable solid.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

(Contd. on page 14)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.05.2025 Version number 02-02 (replaces version 02-01) Revision: 07.05.2025

Trade name: CWS WERTLACK® Metallisé

		(Contd. of page 13)		
H314	Causes severe skin burns and eye damage.			
H315	Causes skin irritation.			
H317	May cause an allergic skin reaction.			
H318	Causes serious eye damage.			
H319	Causes serious eye irritation.			
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.			
H335	May cause respiratory irritation.			
H336	May cause drowsiness or dizziness.			
H351	Suspected of causing cancer.			
H361d	Suspected of damaging the unborn child.			
H372	Causes damage to organs through prolonged or repeated exposure.			
H411	Toxic to aquatic life with long lasting effects.			
EUH066 Repeated exposure may cause skin dryness or cracking.				
EUH071 Corrosive to the respiratory tract.				

Classification according to Regulation (EC) No 1272/2008		
Flammable liquids	On basis of test data	
Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.	

**Date of previous version:** 06.05.2025 **Version number of previous version:** 02-01

## Abbreviations and acronyms:

Flam. Liq. 3: Flammable liquids – Category 3 Flam. Sol. 1: Flammable solids – Category 1

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

Carc. 2: Carcinogenicity - Category 2

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

\* Data compared to the previous version altered.

DE/EN